

Ficha técnica :


# ME 435 FOB



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Métrico                  |
|-------|-----------------------------------------------------------------|-----------|--------------------------|
| 1.1   | Manufacturer                                                    |           | Manitou                  |
| 1.2   | Model Name                                                      |           | ME 435 FOB               |
| 1.3   | Power source                                                    |           | Electrical               |
| 1.4   | Operator type                                                   |           | Seated                   |
| 1.5   | Max. capacity                                                   | Q         | 3500 kg                  |
| 1.6   | Load center of gravity                                          | c         | 500 mm                   |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 445 mm                   |
| 1.9   | Wheelbase                                                       | y         | 1750 mm                  |
|       | <b>Weight</b>                                                   |           |                          |
| 2.1   | Service weight                                                  |           | 5550 kg                  |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 8050 kg / 1000 kg        |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 2720 kg / 2830 kg        |
|       | <b>Wheels</b>                                                   |           |                          |
| 3.1   | Tires type                                                      |           | Solid tires              |
| 3.2   | Dimensions of front wheels                                      |           | 23 x 10 -12              |
| 3.3   | Dimensions of rear wheels                                       |           | 200/50 - 10              |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 2                    |
| 3.5.2 | Number of drive wheels                                          |           | 2                        |
| 3.6   | Front wheel gauge                                               | b10       | 1085 mm                  |
| 3.7   | Rear wheel gauge                                                | b11       | 960 mm                   |
|       | <b>Dimensions</b>                                               |           |                          |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2240 mm                  |
| 4.8   | Seat height/stand height                                        | h7        | 1190 mm                  |
| 4.12  | Height of towing bar (coupling height)                          | h10       | 625 mm                   |
| 4.19  | Overall length                                                  | l1        | 3650 mm                  |
| 4.20  | Length to face of forks                                         | l2        | 2500 mm                  |
| 4.21  | Overall width                                                   | b1        | 1315 mm                  |
| 4.22  | Forks section / width / length                                  | s / e / l | 50 mm x 122 mm x 1150 mm |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 3A                       |
| 4.24  | Fork carriage width                                             | b3        | 1100 mm                  |
| 4.31  | Ground clearance below mast                                     | m1        | 112 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 115 mm                   |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 4045 mm                  |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4245 mm                  |
| 4.35  | Turning radius                                                  | Wa        | 2400 mm                  |
| 4.36  | Internal turning radius (over tyres)                            | b13       | 730 mm                   |
|       | <b>Performances</b>                                             |           |                          |
| 5.1   | Travel speed (laden / unladen)                                  |           | 19 km/h-20 km/h          |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.39 m/s-0.54 m/s        |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.47 m/s-0.42 m/s        |
| 5.5   | Drawbar pull (Laden / Unladen)                                  |           | 1690 daN / 1700 daN      |
| 5.7   | Gradeability (laden / unladen)                                  |           | 12 % / 18 %              |
| 5.10  | Service brake                                                   |           | Oil bath                 |
|       | <b>Engine</b>                                                   |           |                          |
| 6.1   | Drive motor rating S2 60 min                                    |           | 18.50 kW                 |
| 6.2   | Lift motor rating at S3 15%                                     |           | 25.40 kW                 |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43536 A               |
| 6.4   | Battery voltage / capacity                                      |           | 80 V / 700 Ah            |
| 6.6   | Energy consumption                                              |           | 12.50 kWh                |
|       | <b>Miscellaneous</b>                                            |           |                          |
| 8.1   | Type of drive control                                           |           | Electronic               |
| 8.2   | Working hydraulic pressure for attachments                      |           | 210 bar                  |
| 8.3   | Oil flow rate for attachments                                   |           | 65 l/min                 |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 74 dB                  |

## ME 435 FOB - Diagrama dimensional



# Características de los mástiles y capacidad residual

| Full Visibility Duplex (FVD)                               |    | FVD 30 | FVD 33 | FVD 35 | FVD 37 | FVD 40 | FVD 43 | FVD 45 | FVD 48 | FVD 50 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      | 8      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2235   | 2385   | 2485   | 2858   | 2835   | 2985   | 3085   | 3235   | 3335   |
| h2 - Mast free lift                                        | mm | 150    | 150    | 150    | 150    | 150    | 150    | 150    | 150    | 150    |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |
| h4 - Mast extended height                                  | mm | 3838   | 4138   | 4338   | 4538   | 4838   | 5138   | 5338   | 5638   | 5838   |
| Residual capacity at max height                            | kg | 3500   | 3500   | 3500   | 3500   | 3500   | 3500   | 3500   | 3500   | 3400   |
| Residual capacity with integrated side shift at max height | kg | 3500   | 3500   | 3500   | 3500   | 3500   | 3500   | 3400   | 3350   | 3400   |
| Residual capacity with hooked-on side shift at max height  | kg | 3500   | 3500   | 3500   | 3500   | 3500   | 3500   | 3400   | 3300   | 3200   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4000   | 4000   | 4000   |

| Free Lift Duplex (FLD)                                     |    | FLD 30 | FLD 33 | FLD 37 | FLD 40 |
|------------------------------------------------------------|----|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      |
| h1 - Mast lowered height                                   | mm | 2135   | 2285   | 2485   | 2685   |
| h2 - Mast free lift                                        | mm | 1275   | 1425   | 1625   | 1825   |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3700   | 4000   |
| h4 - Mast extended height                                  | mm | 3860   | 4160   | 4560   | 4860   |
| Residual capacity at max height                            | kg | 3500   | 3500   | 3500   | 3500   |
| Residual capacity with integrated side shift at max height | kg | 3500   | 3500   | 3500   | 3500   |
| Residual capacity with hooked-on side shift at max height  | kg | 3500   | 3500   | 3500   | 3500   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3700   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3700   | 4000   |

| Free Lift Triplex (FLT)                                    |    | FLT 40 | FLT 43 | FLT 48 | FLT 50 | FLT 55 | FLT 60 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2135   | 2235   | 2435   | 2535   | 2735   | 2985   |
| h2 - Mast free lift                                        | mm | 1275   | 1375   | 1575   | 1675   | 1875   | 2125   |
| h3 - Mast lifting height                                   | mm | 4000   | 4300   | 4800   | 5000   | 5500   | 6000   |
| h4 - Mast extended height                                  | mm | 4680   | 5160   | 5660   | 5860   | 6360   | 6860   |
| Residual capacity at max height                            | kg | 3500   | 3400   | 3300   | 3200   | 3150   | 3000   |
| Residual capacity with integrated side shift at max height | kg | 3500   | 3350   | 3250   | 3200   | 3150   | 3000   |
| Residual capacity with hooked-on side shift at max height  | kg | 3400   | 3250   | 3100   | 3050   | 3000   | 2850   |
| Height at max capacity                                     | mm | 2500   | 2500   | 2500   | 2500   | 2500   | 2500   |



**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes