

Technical sheet :

ME 430 US



Technical characteristics			Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		ME 430 US	ME 430 US
1.3	Power source		Electrical - Lead	Electrical - Lead
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	3000 kg	6614 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	445 mm	18 in
1.9	Wheelbase	y	1750 mm	69 in
Weight				
2.1	Service weight		5250 kg	11574 lb
2.2	Weight on front axle (laden) / rear axle (laden)		7340 kg / 980 kg	16182 lb / 2161 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2572 kg / 2578 kg	5670 lb / 5684 lb
Wheels				
3.1	Tires type		Solid tires	Solid tires
3.2	Dimensions of front wheels		23 x 9-10	23 x 9-10
3.3	Dimensions of rear wheels		18 x 7-8	18 x 7-8
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	1073 mm	42 in
3.7	Rear wheel gauge	b11	960 mm	38 in
Dimensions				
4.8	Seat height/stand height	h7	1190 mm	47 in
4.7	Height of overhead guard (cabin)	h6	2240 mm	88 in
4.12	Height of towing bar (coupling height)	h10	625 mm	25 in
4.19	Overall length	l1	3645 mm	144 in
4.20	Length to face of forks	l2	2495 mm	98 in
4.21	Overall width	b1	1275 mm	50 in
4.22	Forks section / width / length	s / e / l	45 mm x 122 mm x 1150 mm	2 in x 5 in x 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A	3A
4.24	Fork carriage width	b3	1100 mm	43 in
4.31	Ground clearance below mast	m1	105 mm	4 in
4.32	Ground clearance at centre of wheelbase	m2	115 mm	5 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4045 mm	159 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4245 mm	167 in
4.35	Turning radius	Wa	2400 mm	94 in
4.36	Internal turning radius (over tyres)	b13	730 mm	29 in
Performances				
5.1	Travel speed (laden / unladen)		19 km/h-20 km/h	12 mph-12 mph
5.2	Lifting speed (laden / unladen)		0.42 m/s-0.54 m/s	1 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		0.47 m/s-0.42 m/s	2 ft/s-1 ft/s
5.5	Drawbar pull (Laden / Unladen)		1740 daN / 1680 daN	1740 daN / 1680 daN
5.7	Gradeability (laden / unladen)		14 % / 20 %	14 % / 20 %
5.10	Service brake		Oil bath	Oil bath
Engine				
6.1	Drive motor rating S2 60 min		18.50 kW	18.50 kW
6.2	Lift motor rating at S3 15%		25.40 kW	25.40 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43536 A	DIN43536 A
6.4	Battery voltage / capacity		80 V / 700 Ah	80 V / 700 Ah
6.6	Energy consumption according to VDI cycle (kWh/h)		11.50 kWh/h	11.50 kWh/h
Miscellaneous				
8.1	Type of drive control		Electronic	Electronic
8.2	Working hydraulic pressure for attachments		210 bar	3046 PSI
8.3	Oil flow rate for attachments		65 l/min	17 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 72 dB	< 72 dB
8.4	Sound level at the driver's ear according to DIN 12 053		72 dB	72 dB

ME 430 US - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 43	FVD 45	FVD 48	FVD 50
α - Mast/fork carriage tilt, forward	°	5	5	5	5	5	5	5	5	5
β - Mast/fork carriage tilt, backward	°	8	8	8	8	8	5	5	5	5
h1 - Mast lowered height	in (mm)	88 (2235)	93.9 (2385)	97.8 (2485)	11.2 (285)	111.6 (2835)	117.5 (2985)	121.5 (3085)	127.4 (3235)	131.3 (3335)
h2 - Mast free lift	in (mm)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)
h3 - Mast lifting height	in (mm)	118.1 (3000)	129.9 (3300)	137.8 (3500)	145.7 (3700)	157.5 (4000)	169.3 (4300)	177.2 (4500)	189 (4800)	196.9 (5000)
h4 - Mast extended height	in (mm)	151.1 (3838)	162.9 (4138)	170.8 (4338)	178.7 (4538)	190.5 (4838)	202.3 (5138)	210.2 (5338)	222 (5638)	229.8 (5838)
Residual capacity at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with integrated side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with hooked-on side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6504 (2950)	6393 (2900)	6173 (2800)
Height at max capacity	in (mm)	118.1 (3000)	129.9 (3300)	137.8 (3500)	145.7 (3700)	157.5 (4000)	169.3 (4300)	177.2 (4500)	189 (4800)	196.9 (5000)
Height at max capacity with integrated sideshift	in (mm)	118.1 (3000)	129.9 (3300)	137.8 (3500)	145.7 (3700)	157.5 (4000)	169.3 (4300)	177.2 (4500)	189 (4800)	196.9 (5000)

Free Lift Duplex (FLD)		FLD 30	FLD 33	FLD 37	FLD 40
α - Mast/fork carriage tilt, forward	°	5	5	5	5
β - Mast/fork carriage tilt, backward	°	8	8	8	8
h1 - Mast lowered height	in (mm)	84.1 (2135)	90 (2285)	97.8 (2485)	105.7 (2685)
h2 - Mast free lift	in (mm)	50.2 (1275)	56.1 (1425)	64 (1625)	71.9 (1825)
h3 - Mast lifting height	in (mm)	118.1 (3000)	129.9 (3300)	145.7 (3700)	157.5 (4000)
h4 - Mast extended height	in (mm)	152 (3860)	163.8 (4160)	179.5 (4560)	191.3 (4860)
Residual capacity at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with integrated side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with hooked-on side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)
Height at max capacity	in (mm)	118.1 (3000)	129.9 (3300)	145.7 (3700)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	118.1 (3000)	129.9 (3300)	145.7 (3700)	157.5 (4000)

Free Lift Triplex (FLT)		FLT 40	FLT 43	FLT 48	FLT 50	FLT 55	FLT 60
α - Mast/fork carriage tilt, forward	°	5	5	5	5	5	5
β - Mast/fork carriage tilt, backward	°	5	5	5	5	5	5
h1 - Mast lowered height	in (mm)	80.1 (2035)	84.1 (2135)	90 (2285)	93.9 (2385)	101.8 (2585)	111.6 (2835)
h2 - Mast free lift	in (mm)	49.2 (1250)	53.1 (1350)	59.1 (1500)	63 (1600)	70.9 (1800)	80.7 (2050)
h3 - Mast lifting height	in (mm)	157.5 (4000)	169.3 (4300)	189 (4800)	196.9 (5000)	216.5 (5500)	236.2 (6000)
h4 - Mast extended height	in (mm)	188.4 (4785)	200.2 (5085)	219.9 (5585)	227.8 (5785)	247.4 (6285)	267.1 (6785)
Residual capacity at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6614 (3000)	6393 (2900)	5952 (2700)
Residual capacity with integrated side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)	6393 (2900)	6173 (2800)	5842 (2650)
Residual capacity with hooked-on side shift at max height	lb (kg)	6393 (2900)	6393 (2900)	6283 (2850)	6063 (2750)	5622 (2550)	5401 (2450)
Height at max capacity	in (mm)	157.5 (4000)	169.3 (4300)	189 (4800)	196.9 (5000)	157.5 (4000)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	157.5 (4000)	169.3 (4300)	189 (4800)	157.5 (4000)	157.5 (4000)	157.5 (4000)



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes