

Technical sheet :


MI 25 G US



 **MANITOU**
HANDLING YOUR WORLD

| Technical characteristics | | Imperial | |
|---------------------------|---|-----------|-----------------------|
| 1.1 | Manufacturer | | Manitou |
| 1.2 | Model Name | | MI 25 G US |
| 1.3 | Power source | | LPG |
| 1.4 | Operator type | | Seated |
| 1.5 | Max. capacity | Q | 5512 lb |
| 1.6 | Load center of gravity | c | 20 in |
| 1.8 | Load distance, centre of drive axle to fork | x | 18 in |
| 1.9 | Wheelbase | y | 63 in |
| | Standard mast reference of the machine | | FVD 33 |
| Weight | | | |
| 2.1 | Service weight | | 8587 lb |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 12489 lb / 1609 lb |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 3671 lb / 4916 lb |
| Wheels | | | |
| 3.1 | Tires type | | Solid tires |
| 3.2 | Dimensions of front wheels | | 7.00-12 12 |
| 3.3 | Dimensions of rear wheels | | 6.00-9 10 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 38 in |
| 3.7 | Rear wheel gauge | b11 | 38 in |
| Dimensions | | | |
| 4.8 | Seat height/stand height | h7 | 47 in |
| 4.7 | Height of overhead guard (cabin) | h6 | 83 in |
| 4.12 | Height of towing bar (coupling height) | h10 | 14 in |
| 4.19 | Overall length | l1 | 145 in |
| 4.20 | Length to face of forks | l2 | 100 in |
| 4.21 | Overall width | b1 | 45 in |
| 4.21 | Overall width - Single wheels | b1 | 45 in |
| 4.22 | Forks section / width / length | s / e / l | 2 in x 5 in x 45 in |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | 2A |
| 4.24 | Fork carriage width | b3 | 41 in |
| 4.31 | Ground clearance below mast | m1 | 5 in |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 7 in |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 155 in |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 163 in |
| 4.35 | Turning radius | Wa | 89 in |
| 4.36 | Internal turning radius (over tyres) | b13 | 6 in |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 12 mph-12 mph |
| 5.2 | Lifting speed (laden / unladen) | | 2 ft/s-2 ft/s |
| 5.3 | Lowering speed (laden / unladen) | | 2 ft/s-2 ft/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 1700 daN / 1040 daN |
| 5.7 | Gradeability (laden / unladen) | | 20 % / 20 % |
| 5.10 | Service brake | | Hydraulic |
| | Transmission type | | Torque converter |
| Engine | | | |
| 7.1 | Engine brand / model | | GCT (ex-Nissan) / K25 |
| 7.2 | Engine power (Hp / kW) | | 63 Hp/46 kW |
| 7.3 | Rated speed | | 2400 rpm |
| 7.4 | Number of cylinders / Capacity of cylinders | | 4 - 152 in³ |
| Miscellaneous | | | |
| 8.2 | Working hydraulic pressure for attachments | | 2321 PSI |
| 8.3 | Oil flow rate for attachments | | 19 US gpm |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 80 dB |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | 80 dB |

MI 25 G US - Dimensional drawing



**Head Office**

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes