

Technical sheet :

# MI 40 G US

---



 **MANITOU**  
HANDLING YOUR WORLD

	Technical characteristics		Imperial
1.1	Manufacturer		Manitou
1.2	Model Name		MI 40 G US
1.3	Power source		Lpg
1.4	Operator type		Seated
1.5	Max. capacity	Q	8818 lb
1.6	Load center of gravity	c	20 in
1.8	Load distance, centre of drive axle to fork	x	22 in
1.9	Wheelbase	y	79 in
	<b>Weight</b>		
2.1	Service weight		13889 lb
2.2	Weight on front axle (laden) / rear axle (laden)		19842 lb / 2866 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		6173 lb / 7716 lb
	<b>Wheels</b>		
3.1	Tires type		Pneumatic
3.2	Dimensions of front wheels		300-15 18PR
3.3	Dimensions of rear wheels		7.00-12-12PR
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		2
3.6	Front wheel gauge	b10	46 in
3.7	Rear wheel gauge	b11	44 in
	<b>Dimensions</b>		
4.7	Height of overhead guard (cabin)	h6	94 in
4.8	Seat height/stand height	h7	54 in
4.12	Height of towing bar (coupling height)	h10	18 in
4.19	Overall length	l1	169 in
4.20	Length to face of forks	l2	121 in
4.21	Overall width	b1	55 in
4.21	Overall width - Single wheels	b1	55 in
4.22	Forks section / width / length	s / e / l	2 in x 5 in x 48 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A
4.24	Fork carriage width	b3	49 in
4.31	Ground clearance below mast	m1	7 in
4.32	Ground clearance at centre of wheelbase	m2	9 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	183 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	188 in
4.35	Turning radius	Wa	109 in
4.36	Internal turning radius (over tyres)	b13	5 in
	<b>Performances</b>		
5.1	Travel speed (laden / unladen)		14 mph-15 mph
5.2	Lifting speed (laden / unladen)		2 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		2 ft/s-2 ft/s
5.5	Drawbar pull (Laden / Unladen)		3800 daN / 2200 daN
5.7	Gradeability (laden / unladen)		24 % / 37 %
5.10	Service brake		Hydraulic
	Transmission type		Torque converter
	<b>Engine</b>		
7.1	Engine brand / model		PSI / 4,3 L
7.2	I.C. Engine power rating		74 kW
7.3	Rated speed		2300 rpm
7.4	Number of cylinders / Capacity of cylinders		6 - 262 in³
	<b>Miscellaneous</b>		
8.2	Working hydraulic pressure for attachments		2321 PSI
8.3	Oil flow rate for attachments		24 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 83 dB

## MI 40 G US - Dimensional drawing



[illegible]



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes