Technical sheet:

## MT 625 H COMFORT






	MT 625 H COMFORT Created on November 1, 2025 at 1:54 PM U
Capacities	Metric
Max. capacity	2500 kg
Max. lifting height	5.85 m
Maximum outreach	3.40 m
Breakout force with bucket	3.40 m
Weight and dimensions	5427 udiv
	111
Overall length to carriage	l11 3.83 m
Length to face of forks	l2 3.90 m
Overall width	b1 1.81 m
Overall height	h17 1.92 m
Wheelbase	y 2.30 m
Ground clearance	m4 0.33 m
Overall cab width	b4 0.79 m
Tilt-up angle	a4 12 °
Tilt-down angle	a5 117°
External turning radius (over tyres)	Wa1 3.31 m
Overall weight	4800 kg
Tires type	Inflatable
Standard tires	CAMSO SKS532 12-16.5
Forks length / width / section	I / e / s 1200 mm x 125 mm x 45 mm
Performances	
Lifting	8 s
Lowering	5.40 s
Extension	5.60 s
Retraction	4.30 s
Crowd	3.50 s
Dump	3.60 s
Engine	
Engine brand	Kubota
Engine norm	Stage V, Tier 4 final
Engine model	V3307-CR-TE5B
Number of cylinders / Capacity of cylinders	4 - 3331 cm <sup>3</sup>
Engine power (Hp/kW)	75 Hp / 55.40 kW
Max. torque / Engine rotation	
	265 Nm @ 1400 rpm 3550 daN
Drawbar pull (Laden) Electric circuit	3330 dain
	110 Al-
12V Battery capacity	110 Ah
Transmission	Understation
Transmission type	Hydrostatic
Number of gears (forward / reverse)	2/2
Max. travel speed	24.90 km/h
Max. travel speed (may vary according to applicable regulations)	25 km/h
Parking brake	Automatic negative parking brake
Service brake	Oil-Immersed multi-discs braking on front axles
Axle Manufacturer	Dana
Hydraulics	
Hydraulic pump type	Gear pump
Hydraulic flow / Pressure	90 I/min-235 bar
Tank capacities	
Engine oil	11.20
Hydraulic oil	115
Fuel	63
Noise and vibration	
Noise at driving position (LpA)	76 dB
Noise to environment (LwA)	104 dB
Vibration on hands/arms	< 2.50 m/s <sup>2</sup>
Miscellaneous	
Steering wheels (front / rear)	2/2
Drive wheels (front / rear)	2/2
Safety / Cab certification	Standard EN 15000 / ROPS - FOPS cab (level 1)
Controls	JSM
- Onition - Onit	JOIN

## MT 625 H Comfort - Load chart

## Machine on tires with forks Metric







## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes