GCT 3-14 GCT




GEHL.

round clearance not be retailed as width the page of t	Metric	
ax. utreach ax. outreach reakout force with bucket leight and dimensions lheelbase round clearance verall cab width It-up angle it-down angle ternal turning radius (over tyres) verall weight erformances rowd ump ngine ngine brand ngine norm ngine model umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake evorable vorable vo	Medic	
ax. outreach reakout force with bucket relegit and dimensions round clearance round clearance reverall cab width thup angle the down angle reternal turning radius (over tyres) werall weight reformances rowd rump refine rengine brand regine norm regine model rumber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type rumber of gears (forward / reverse) rarking brake revice brake	1250 kg	
reakout force with bucket leight and dimensions theelbase round clearance round grants tert and shift but but but but but but but but but bu	4.30 m	
reight and dimensions Theelbase round clearance verall cab width the unangle tt-down angle cternal turning radius (over tyres) verall weight reformances rowd rump ragine rigine porant rigine norm rigine model rumber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type ransmission type reforable reformace revice brake revice brake revice brake revice brake revice brake revice brake reverall width be reformance ransmission rand radius reformance ransmission	2.62 m	
Theelbase round clearance round ro	1880 daN	
round clearance verall cab width It-up angle It-down angle It-d		
verall cab width It-up angle It-down angle It-do	/ 2.13 m	
It-up angle It-down angle It-d	14 0.29 m	
Itt-down angle Itt-down angle Itt down angle	4 0.66 m	
Acternal turning radius (over tyres) Verall weight Performances Prowd Pump Pagine Pagine Pagine brand Pagine porm Pagine porm Pagine power rating - Power Pax. torque / Engine rotation Prawbar pull (Laden) Vo validated (according to EN 15940 standard) Pransmission Pransmission type Pumber of gears (forward / reverse) Parking brake Pervice brake Pydraulics	4 23 °	
verall weight erformances rowd ump ngine ngine ngine brand ngine norm ngine model umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydrautics	5 116 °	
erformances rowd ump ngine ngine ngine brand ngine model umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	a1 2.62 m	
rowd ump Ingine Ingine Ingine Ingine brand Ingine model Ingine model Ingine model Ingine power rating - Power Ingine power rating - Power Ingine rotation Ing	2750 kg	
ump Ingine Ingine Ingine Ingine brand Ingine model Ingine model Ingine power rating - Power Ingine power rating - Power Ingine rotation Ingine rotation Ingine rotation Ingine rotation Ingine rotation Ingine rotation Ingine power rating - Power Ingine po		
Ingine Ingine brand Ingine norm Ingine model It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders It is g	3.40 s	
Ingine Ingine brand Ingine norm Ingine model It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders / Capacity of cylinders It is graph of cylinders It is g	2.60 s	
ngine brand ngine model umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics		
ragine norm Ingine model It is a power rating - Power It is a power rating - P	Yanmar	
raine model umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	Stage V / Tier 4 fin	al
umber of cylinders / Capacity of cylinders C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	3TNV88C-DMU	
C. Engine power rating - Power ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	3 - 1642 cm ³	
ax. torque / Engine rotation rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	35.10 Hp / 26.20 kV	٧
rawbar pull (Laden) VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydraulics	105 Nm @ 1950 rpi	
VO validated (according to EN 15940 standard) ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydrautics	2000 daN	
ransmission ransmission type umber of gears (forward / reverse) arking brake ervice brake ydrautics	Yes	
umber of gears (forward / reverse) arking brake ervice brake ydrautics		
umber of gears (forward / reverse) arking brake ervice brake ydrautics	Hydrostatic	
arking brake ervice brake ydrautics	2/2	
ervice brake ydraulics	Automatic negative parki	ng brake
ydraulics	Hydraulic servo bra	-
	,	
V L . V	Gear pump	
ydraulic flow / Pressure	48 l/min-235 bar	
ank capacities	15 Q IIII 255 But	
ydraulic oil	39 l	
uel tank	35 l	
iscellaneous	33 (
afety cab homologation	ROPS - FOPS level 1	cah
ontrols	Joystick	

GCT 3-14 - Load chart

Machine on tyres with forks Metric







Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend