

# GCT 3-14+

CONSTRUCTION TELEHANDLERS



## Key Features

- ✓ Multi-Function Joystick on Floating Armrest
- ✓ Automatic Parking Brake
- ✓ Harmony Display
- ✓ Polycarbonate Roof Window
- ✓ Hydrostatic Transmission, 2-Speed
- ✓ 3 Steering Modes
- ✓ Articulated Rod
- ✓ Battery Cut-Off

## SPEZIFIKATIONEN

METRISCH		
Capacities	Max. capacity	1500 kg
	Max. lifting height	4.30 m
	Max. outreach	2.62 m
	Breakout force with bucket	1880 daN
	Reach at max. height	1 m
Weight and dimensions	Overall length to carriage (with hitch)	3.47 m
	Overall length to carriage (without hitch)	3.47 m
	Front overhang	0.77 m
	Overall width	1.49 m
	Overall height	1.92 m
	Wheelbase	2.13 m
	Ground clearance	0.29 m
	Overall cab width	0.66 m
	Tilt-up angle	23 °
	Tilt-down angle	116 °
	External turning radius (over tyres)	2.62 m
	Shipping mass (min. / max.)	2700 kg / 2900 kg
	Standard tires	CAMSO - MPT 552 - 10.0/75-15.3 124A8
Performances	Lifting	8.80 s
	Lowering	7 s
	Extension	6.40 s
	Retraction	4.30 s
	Crowd	3.40 s
	Dump	2.60 s
Engine	Engine brand	Yanmar
	Engine norm	Stage V / Tier 4 final
	Engine model	3TNV88C-DMU
	Number of cylinders / Capacity of cylinders	3 - 1642 cm³
	I.C. Engine power rating - Power	35.10 Hp / 26.20 kW
	Max. torque / Engine rotation	105 Nm @ 1950 rpm
	Drawbar pull (Laden)	2000 daN
HVO validated (according to EN 15940 standard)	Ja	
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	25 km/h
	Parking brake	Automatic negative parking brake
	Service brake	Hydraulic servo brake
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	48 l/min-235 bar
Tank capacities	Hydraulic oil	39 l
	Hydraulic tank capacity	39 l
	Fuel tank	35 l
Noise and vibration	Noise to environment (LwA)	104 dB
	Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	Safety cab homologation	ROPS - FOPS cab (level 1)
	Controls	Joystick



## STANDARDMERKMALE

- Crab mode
- Battery cut-off
- USB Plug
- Two-Speed Hydrostatic Drive System
- Harmony screen
- Automatic parking brake
- 12Volt Power Port
- Document holder
- Connected machine
- 4 wheel drive

## OPTIONALE MERKMALE

- Attachment hydraulic line
- Air prefilter
- Adjustable and telescopic steering column
- Stop & Start
- Air suspension cloth-covered seat (GRAMMER)
- Auto Reversing Fan
- LED work lights on the boom (x2)
- Continuous flow hydraulics
- Front and rear LED work lights on cab (x4 : 2 front + 2 rear)
- Attachment hydraulic locking
- Air Conditioning



One Gehl Way, West Bend, WI 53095  
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.