
GCT 3-14+ GCT





GEHL®

Capacities		Metric	
Max. capacity		1500 kg	
Max. lifting height		4.30 m	
Max. outreach		2.62 m	
Breakout force with bucket		1880 daN	
Weight and dimensions			
Overall length to carriage	l11	3.47 m	
Overall width	b1	1.49 m	
Overall height	h17	1.92 m	
Wheelbase	у	2.13 m	
Ground clearance	m4	0.29 m	
Overall cab width	b4	0.66 m	
Tilt-up angle	a4	23 °	
Tilt-down angle	a5	116 °	
External turning radius (over tyres)	Wa1	2.62 m	
Unladen weight		2700 kg	
Performances			
Crowd		3.40 s	
Dump		2.60 s	
Engine			
Engine brand		Yanmar	
Engine norm	St	age V / Tier 4 final	
Engine model		3TNV88C-DMU	
Number of cylinders / Capacity of cylinders		3 - 1642 cm ³	
I.C. Engine power rating - Power	3.	5.10 Hp / 26.20 kW	
Max. torque / Engine rotation		105 Nm @ 1950 rpm	
Drawbar pull (Laden)		2000 daN	
HVO validated (according to EN 15940 standard)		Yes	
Transmission			
Transmission type		Hydrostatic	
Number of gears (forward / reverse)		2/2	
Travel speed (laden)		25 km/h	
Max. travel speed		25 km/h	
Parking brake	Automat	ic negative parking brake	
Service brake		draulic servo brake	
Hydraulics			
Hydraulic pump type		Gear pump	
Hydraulic Pressure		235 bar	
Tank capacities			
Hydraulic oil		39 l	
Fuel tank		35 l	
Noise and vibration			
Vibration on hands/arms		< 2.50 m/s ²	
Miscellaneous			
Safety cab homologation	ROF	S - FOPS level 1 cab	
Controls		Joystick	

GCT 3-14+ - Dimensional drawing








GCT 3-14+ - Load chart

Machine on tyres with forks Metric







Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend