Technical sheet:

MT 935 75D ST5







	MT 935 75D ST5 Created on October 31, 2025 at 12:41	PIVI U I
Capacities	Metric	
Max. capacity	3500 kg	
Max. lifting height	9 m	
Maximum outreach	6.40 m	
Breakout force with bucket	7180 daN	
Weight and dimensions		
Overall length to carriage	l11 4.70 m	
Length to face of forks	l2 4.78 m	
Overall length (with forks)	l1 5.98 m	
Overall width	b1 2.27 m	
Overall height	h17 2.48 m	
Wheelbase	y 2.80 m	
Ground clearance	m4 0.42 m	
Overall cab width	b4 0.95 m	
Tilt-up angle	a4 13 °	
Tilt-down angle	a5 114 °	
External tuming radius	Wa3 3.77 m	
External turning radius (over tyres)	Wa1 3.78 m	
Unladen weight (with forks)	7480 kg	
Overall weight	7480 kg	
Tires type	Inflatable	
Standard tires	Alliance 400/80 - 24 - 162A8	
Forks length / width / section	I / e / s 1200 mm x 100 mm x 50 mm	
Performances		
Lifting	7.20 s	
Lowering	4.70 s	
Extension	11 s	
Retraction	7 s	
Crowd	3 s	
Dump	3.40 s	
Engine		
Engine brand	Deutz	
Engine norm	Stage V / Tier 4 Final	
Engine model	TCD 2.9I 2501-7118	
Number of cylinders / Capacity of cylinders	4 - 2924 cm³	
Engine power (Hp/kW)	75 Hp / 55.40 kW	
Max. torque / Engine rotation	375 Nm @ 1400 rpm	
Drawbar pull (Laden)	7220 daN	
HVO validated (according to EN 15940 standard)	Yes	
Electric circuit		
12V Battery capacity	110 Ah	
Transmission		
Transmission type	Torque converter	
Number of gears (forward / reverse)	4 / 4	
Max. travel speed	24.70 km/h	
Max. travel speed (may vary according to applicable regulations)	24.90 km/h	
	Automatic parking brake	
Parking brake		
Service brake	Hydraulic servo brake	
Hydraulics		
Hydraulic pump type	Axial piston	
Hydraulic flow / Pressure	110 l/min-270 bar	
Tank capacities		
Engine oil	8.50 1	
Hydraulic oil	145	
uel tank	103 I	
Noise and vibration		
Noise at driving position (LpA)	77 dB	
Noise to environment (LwA)	104 dB	
Vibration on hands/arms	< 2.50 m/s²	
Miscellaneous		
Steering wheels (front / rear)	2/2	
Drive wheels (front / rear)	2/2	
Safety / Cab certification	Standard EN 15000 / Cabin ROPS - FOPS	level 2
Controls	JSM	

MT 935 75D ST5 - Dimensional drawing








MT 935 75D ST5 - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes