

Technical sheet :


MT 1135 75 D



 **MANITOU**
HANDLING YOUR WORLD


Capacities		Metric	
Max. capacity		3500 kg	
Max. lifting height		10.90 m	
Maximum outreach		7.20 m	
Breakout force with bucket		6850 daN	
Weight and dimensions			
Overall length to carriage	I11	5.14 m	
Length to face of forks	I2	5.14 m	
Overall length (with forks)	I1	6.34 m	
Overall width	b1	2.26 m	
Overall height	h17	2.48 m	
Wheelbase	y	2800 mm	
Ground clearance	m4	0.42 m	
Overall cab width	b4	0.95 m	
Tilt-up angle	a4	13 °	
Tilt-down angle	a5	114 °	
External turning radius	Wa3	3.77 m	
External turning radius (over tyres)	Wa1	3.77 m	
Unladen weight (with forks)		8360 kg	
Overall weight		8360 kg	
Tires type		Inflatable	
Standard tires		Alliance 400/80 - 24 - 162A8	
Forks length / width / section	I / e / s	1200 mm x 100 mm x 50 mm	
Performances			
Lifting		7.60 s	
Lowering		5.40 s	
Extension		12.30 s	
Retraction		8.20 s	
Crowd		3.10 s	
Dump		3.60 s	
Engine			
Engine brand		Deutz	
Engine norm		Stage V	
Engine model		TCD 2.9L	
Number of cylinders / Capacity of cylinders		4 - 2924 cm³	
Engine power (Hp/kW)		75 Hp / 55.40 kW	
Max. torque / Engine rotation		375 Nm @ 1400 rpm	
Drawbar pull (Laden)		6000 daN	
Transmission			
Transmission type		Torque converter	
Number of gears (forward / reverse)		2 / 2	
Max. travel speed		24.90 km/h	
Parking brake		Automatic parking brake	
Service brake		Hydraulic servo brake	
Hydraulics			
Hydraulic pump type		Axial piston	
Hydraulic Pressure		270 bar	
Tank capacities			
Engine oil		8.50 l	
Hydraulic oil		149 l	
Fuel		137 l	
Noise and vibration			
Noise at driving position (LpA)		77 dB	
Noise to environment (LwA)		104 dB	
Vibration on hands/arms		2.50 m/s²	
Miscellaneous			
Steering wheels (front / rear)		2 / 2	
Drive wheels (front / rear)		2 / 2	
Safety / Cab certification		Standard EN 15000 / Cabin ROPS - FOPS level 2	
Controls		JSM	

MT 1135 75 D - Dimensional drawing




MT 1135 75 D - Load chart


Machine on tires with forks Metric



Machine on lowered stabilisers with forks Metric



Load Chart metric



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes