Technical sheet:


TMT 25 S Y ST5






		TMT 25 S Y ST5 Crea	ited on November 4, 2025 at 4:42 AM
	Technical characteristics		Metric
1.1	Manufacturer		MANITOU
1.2	Model Name		TMT 25 S Y ST5
1.2.1	Reach out equipment		Telescopic boom
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	2500 kg
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	X	-505 mm
1.9	Wheelbase	V	1651 mm
1.5	Weight	,	1031 11111
2.1	Service weight		2610 kg
2.1	Wheels		2010 Kg
3.1			Pneumatic
	Tires type		
3.2	Dimensions of front wheels		10x16,5
3.3	Dimensions of rear wheels		10x16,5
3.5	Number of front wheels / rear wheels		2/1
.5.2	Drive wheels (front / rear)		2/1
3.6	Front wheel gauge	b10	2072 mm
	Dimensions		
4.1	Mast/fork carriage tilt, forward	α	100 °
.1.1	Mast/fork carriage tilt, backward	β	12 °
4.2	Height telescopic boom lowered	h1	2240 mm
4.3	Mast free lift	h2	1440 mm
4.4	Max. lifting height	h3	3380 mm
4.5	Height telescopic boom extended	h4	3925 mm
4.7	Height of overhead guard (cabin)	h6	2200 mm
4.8	Seat height/stand height	h7	1220 mm
4.19	Overall length	l1	2790 mm
1.20	Length to face of forks	12	1590 mm
1.21	Overall width	b1	2350 mm
4.22	Forks section / width / length	s / e / l	40 mm x 125 mm x 1200 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		FEM 2A
4.24	Fork carriage width	b3	1270 mm
1.26	Distance between support arms	b5	1267 mm
1.26	Distance between wheel arms/loading surfaces	b4	1519 mm
1.28	Maximum horizontal extension at COG 600	14	1310 mm
1.32	Ground clearance at centre of wheelbase	m2	290 mm
1.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	3968 mm
1.34	Aisle width for 800 x 1200 pallet lengthways	Ast	3968 mm
1.35	Turning radius	Wa	3072 mm
	Performances		
5.1	Travel speed (laden / unladen)		11.80 km/h - 11.50 km/h
5.2	Lifting speed (laden / unladen)		0.25 m/s / 0.27 m/s
5.3	Lowering speed (laden / unladen)		0.29 m/s / 0.32 m/s
5.9	Acceleration time (laden / unladen)		4 s / 3.50 s
5.10	Service brake		Hydraulic brakes by loss of pressure
,,,,	Engine		rijalaano siakee sy leece er pieceale
7.1	Engine brand / norm / model		Yanmar - Stage V / 3TNV 86 CT
7.1	Engine power (Hp / kW)		42 Hp / 31 kW
7.3	Rated speed		2800 rpm
	•		· ·
7.4	Number of cylinders / Capacity of cylinders		3 - 1568 cm³
0.1	Miscellaneous		p. 1. P.
8.1	Type of drive control		Hydraulic
0.0			270 bar
8.2 8.3	Working hydraulic pressure for attachments Oil flow rate for attachments		44 I/min

TMT 25 S Y ST5 - Dimensional drawing




TMT 25 S Y ST5 - Load chart

Machine on tires with forks Metric



Machine on lowered stabilisers with forks Metric



Equipment

24V 2x7 plug truck connector adapter 3 braked wheels Boom with integrated side shift Extenseur Left-hand safety strap Metallization	
Boom with integrated side shift Extenseur Left-hand safety strap	
Extenseur Left-hand safety strap	
Left-hand safety strap	
• •	
Motellization	
Metallization	
Telescopic Forks	
Three-function FNR handling levers	

Optional Primo seat Protective seat cover Transparent roof protection





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes