

Technical sheet :


TMM 20 ST5



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer	MANITOU	
1.2	Model Name	TMM 20 ST5	
1.2.1	Reach out equipment	Pantograph	
1.3	Power source	Diesel	
1.4	Operator type	Seated	
1.5	Max. capacity	2000 kg	
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	490 mm
1.9	Wheelbase	y	1598 mm
Weight		FWD 30	
2.1	Standard mast reference of the machine		2290 kg
2.2	Service weight		
2.3	Weight on front axle (laden) / rear axle (laden)		3050 kg / 1240 kg
	Weight on front axle (Unladen) / rear axle (Unladen)		1050 kg / 1240 kg
Wheels		Pneumatic	
3.1	Tires type		27x10-12 IC30
3.2	Dimensions of front wheels		27x10-12 IC30
3.3	Dimensions of rear wheels		
3.5	Number of front wheels / rear wheels		2 / 1
3.5.2	Drive wheels (front / rear)		2 / 1
3.6	Front wheel gauge	b10	2151 mm
Dimensions		h3	
4.4	Max. lifting height		4200 mm
4.7	Height of overhead guard (cabin)		2120 mm
4.8	Seat height/stand height		1070 mm
4.19	Overall length		2650 mm
4.21	Overall width		2406 mm
4.22	Forks section / width / length		40 mm x 122 mm x 1200 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		2A
4.24	Fork carriage width		1260 mm
4.26	Distance between support arms		1165 mm
4.26	Distance between wheel arms/loading surfaces		1600 mm
4.28	Maximum horizontal extension at COG 600		1000 mm
4.32	Ground clearance at centre of wheelbase		272 mm
4.34	Aisle width for 800 x 1200 pallet lengthways		3363 mm
4.35	Turning radius		2463 mm
Performances		h6	
5.1	Travel speed (laden / unladen)		9.40 km/h - 9.50 km/h
5.2	Lifting speed (laden / unladen)		0.26 m/s / 0.24 m/s
5.3	Lowering speed (laden / unladen)		0.38 m/s / 0.24 m/s
5.7	Gradeability (laden / unladen)		56 % / 51 %
5.9	Acceleration time (laden / unladen)		4.10 s / 2.60 s
5.10	Service brake		Hydraulic brakes by loss of pressure
	Transmission type		Hydrostatic
Engine		Kubota - Stage V / D1105-E4B-MNT-2	
7.1	Engine brand / norm / model		25 Hp / 18.50 kW
7.2	Engine power (Hp / kW)		3000 rpm
7.3	Rated speed		3 - 1123 cm ³
7.4	Number of cylinders / Capacity of cylinders		
Miscellaneous		Cable	
8.1	Type of drive control		190 bar
8.2	Working hydraulic pressure for attachments		43 l/min
8.3	Oil flow rate for attachments		
8.4	Sound level at the driver's ear according to DIN 12 053		84 dB

TMM 20 ST5 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 36	FVD 42
Residual Capacity (Maximum Height & LC = 500 mm)		h1 - Mast lowered height mm	2352	2702
	Simple Reach	h3 - Mast lifting height mm	3000	3600
	Simple Reach	h4 - Mast extended height mm	4455	5055
	Double Reach	Pantograph reach in kg	2000	2000
	Double Reach	Pantograph reach out with stabilizers kg	1750	1750
	Double Reach	Pantograph reach out without stabilizers kg	1050	1050
	Double Reach	Telescopic forks reach in kg	2000	2000
	Double Reach	Telescopic Forks reach out with stabilizers kg	1300	1300
	Double Reach	Telescopic Forks reach out without stabilizers kg	1100	1100
	Double Reach	Pantograph & TF reach in kg	2000	2000
	Double Reach	Pantograph & TF reach out with stabilizers kg	1100	1100
	Double Reach	Pantograph & TF reach out without stabilizers kg	550	550



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes