

Technical sheet :


# **TMM 25 ST5**



 **MANITOU**  
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer	MANITOU	
1.2	Model Name	TMM 25 ST5	
1.2.1	Reach out equipment	Pantograph	
1.3	Power source	Diesel	
1.4	Operator type	Seated	
1.5	Max. capacity	2500 kg	
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	490 mm
1.9	Wheelbase	y	1598 mm
<b>Weight</b>		FVD 30	
2.1	Standard mast reference of the machine		2340 kg
2.2	Service weight		3585 kg / 1255 kg
2.3	Weight on front axle (laden) / rear axle (laden)		1085 kg / 1255 kg
<b>Wheels</b>		Pneumatic	
3.1	Tires type		27X10-12 IC30
3.2	Dimensions of front wheels		27X10-12 IC30
3.3	Dimensions of rear wheels		2 / 1
3.5	Number of front wheels / rear wheels		2 / 1
3.5.2	Drive wheels (front / rear)		2151 mm
3.6	Front wheel gauge	b10	
<b>Dimensions</b>		4200 mm	
4.4	Max. lifting height	h3	2120 mm
4.7	Height of overhead guard (cabin)	h6	1070 mm
4.8	Seat height/stand height	h7	2650 mm
4.19	Overall length	l1	2406 mm
4.21	Overall width	b1	40 mm x 122 mm x 1200 mm
4.22	Forks section / width / length	s / e / l	2A
4.23	Fork carriage ISO 2328 (class/form) A/B		1260 mm
4.24	Fork carriage width	b3	1165 mm
4.26	Distance between support arms	b5	1600 mm
4.26	Distance between wheel arms/loading surfaces	b4	1000 mm
4.28	Maximum horizontal extension at COG 600	l4	3363 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2463 mm
4.35	Turning radius	Wa	
<b>Performances</b>		10.60 km/h - 10.70 km/h	
5.1	Travel speed (laden / unladen)		0.26 m/s / 0.24 m/s
5.2	Lifting speed (laden / unladen)		0.38 m/s / 0.21 m/s
5.3	Lowering speed (laden / unladen)		50 % / 51 %
5.7	Gradeability (laden / unladen)		4.10 s / 2.60 s
5.9	Acceleration time (laden / unladen)		Hydraulic brakes by loss of pressure
5.10	Service brake		Hydrostatic
<b>Transmission type</b>		Kubota - Stage V / D1105-E4B-MNT-2	
<b>Engine</b>		25 Hp / 18.50 kW	
7.1	Engine brand / norm / model		3000 rpm
7.2	Engine power (Hp / kW)		3 - 1123 cm <sup>3</sup>
7.3	Rated speed		
7.4	Number of cylinders / Capacity of cylinders		
<b>Miscellaneous</b>		Cable	
8.1	Type of drive control		190 bar
8.2	Working hydraulic pressure for attachments		43 l/min
8.3	Oil flow rate for attachments		
8.4	Sound level at the driver's ear according to DIN 12 053		84 dB

## TMM 25 ST5 - Dimensional drawing



## Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 36	FVD 42
Residual Capacity (Maximum Height & LC = 500 mm)		h1 - Mast lowered height mm	2392	2742
	Simple Reach	h3 - Mast lifting height mm	3000	3600
	Simple Reach	h4 - Mast extended height mm	4495	5095
	Double Reach	Pantograph reach in kg	2500	2500
	Double Reach	Pantograph reach out with stabilizers kg	2000	1950
	Double Reach	Pantograph reach out without stabilizers kg	1050	1000
	Double Reach	Telescopic forks reach in kg	2500	2500
	Double Reach	Telescopic Forks reach out with stabilizers kg	1350	1300
	Double Reach	Telescopic Forks reach out without stabilizers kg	1150	1100
	Double Reach	Pantograph & TF reach in kg	2500	2500
	Double Reach	Pantograph & TF reach out with stabilizers kg	1100	1100
	Double Reach	Pantograph & TF reach out without stabilizers kg	550	550



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes