

Technical sheet :

ME 430 LIFT


OXYGEN



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer	Manitou	
1.2	Model Name	ME 430 LIFT	
1.3	Power source	Electrical - Lithium	
1.4	Operator type	Seated	
1.5	Max. capacity	3000 kg	
1.6	Load center of gravity	500 mm	
1.8	Load distance, centre of drive axle to fork	463.50 mm	
1.9	Wheelbase	1650 mm	
	Standard mast reference of the machine	FVD 30	
Weight		Weight	
2.1	Service weight	4610 kg	
2.2	Weight on front axle (laden) / rear axle (laden)	6610 kg / 1000 kg	
2.3	Weight on front axle (Unladen) / rear axle (Unladen)	1960 kg / 2650 kg	
Wheels		Wheels	
3.1	Tires type	Solid tires	
3.2	Dimensions of front wheels	23x10-12-18PR	
3.3	Dimensions of rear wheels	18x7-8-16PR	
3.5	Number of front wheels / rear wheels	2 / 2	
3.5.2	Number of drive wheels	2	
3.6	Front wheel gauge	1044 mm	
3.7	Rear wheel gauge	960 mm	
Dimensions		Dimensions	
4.8	Seat height/stand height	1155 mm	
4.7	Height of overhead guard (cabin)	2186 mm	
4.12	Height of towing bar (coupling height)	440 mm	
4.19	Overall length	3522.50 mm	
4.20	Length to face of forks	2452.50 mm	
4.21	Overall width	1298 mm	
4.22	Forks section / width / length	45 mm x 122 mm x 1070 mm	
4.23	Fork carriage ISO 2328 (class/form) A/B	3A	
4.24	Fork carriage width	1100 m	
4.31	Ground clearance below mast	127 mm	
4.32	Ground clearance at centre of wheelbase	115 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	3854 mm	
4.34	Aisle width for 800 x 1200 pallet lengthways	4053.50 mm	
4.35	Turning radius	2190 mm	
Performances		Performances	
5.1	Travel speed (laden / unladen)	19 km/h-20 km/h	
5.2	Lifting speed (laden / unladen)	0.45 m/s-0.55 m/s	
5.3	Lowering speed (laden / unladen)	0.50 m/s-0.53 m/s	
5.5	Drawbar pull (Laden / Unladen)	850 daN / 950 daN	
5.7	Gradeability (laden / unladen)	13 % / 24 %	
5.10	Service brake	Hydraulic	
Engine		Engine	
6.1	Drive motor rating S2 60 min	20 kW	
6.2	Lift motor rating at S3 15%	26 kW	
6.3	Battery according to DIN 43531/35/36 A, B, C	Lithium	
6.4	Battery voltage / capacity	76.80 V / 460 Ah	
6.5	Battery weight (+/- 5%)	310 kg	
6.6	Energy consumption according to VDI cycle (kWh/h)	8 kWh/h	
Miscellaneous		Miscellaneous	
8.2	Working hydraulic pressure for attachments	160 bar	
8.3	Oil flow rate for attachments	25 l/min	
8.4	Sound level at the driver's ear according to DIN 12 053	70 dB	

ME 430 LIFT - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)	
α - Mast/fork carriage tilt, forward	°
β - Mast/fork carriage tilt, backward	°
h1 - Mast lowered height	mm
h2 - Mast free lift	mm
h3 - Mast lifting height	mm
h4 - Mast extended height	mm
Residual capacity at max height	kg
Residual capacity with integrated side shift at max height	kg

FVD 30	FVD 33	FVD 37	FVD 40	FVD 45
6	6	6	6	6
12	12	12	12	6
2007	2157	2407	2607	2857
145	145	145	145	145
3000	3300	3700	4000	4500
4142	4442	4842	5142	5642
3000	3000	3000	3000	3000
2900	2900	2900	2900	2900

Free Lift Triplex (FLT)	
α - Mast/fork carriage tilt, forward	°
β - Mast/fork carriage tilt, backward	°
h1 - Mast lowered height	mm
h2 - Mast free lift	mm
h3 - Mast lifting height	mm
h4 - Mast extended height	mm
Residual capacity at max height	kg
Residual capacity with integrated side shift at max height	kg

FLT 40	FLT 45	FLT 48	FLT 50	FLT 55	FLT 60	FLT 65
6	6	6	6	3	3	3
6	12	12	6	12	6	6
2007	2157	2307	2407	2607	2857	3057
865	1015	1165	1265	1465	1715	1915
4000	4500	4800	5000	5500	6000	6500
5142	5642	5942	6142	6642	7142	7642
3000	3000	2900	2850	2670	2350	2000
2900	2900	2800	2750	2570	2250	1900

Equipment

Standard

Audio warning on reverse movements

Battery - 35.3kWh - Lithium-ion

Electric parking brake

External charger - 10kW AC - Lithium-ion - Three-phase

LED rear work light

Mechanical suspension PVC seat - Grammer MSG65

Overhead guard - With roof window (Tempered glass)

Panoramic interior rear view mirror

Rear working light

Optional

Battery - 46.7kWh - Lithium-ion

Charger - 20kW - 32A - 380V - Lithium-ion

Closed cab

External charger - 8kW AC - Lithium-ion - Three-phase

Heater

LED blue lamp

LED rear blue lamp

Mini levers - 4 hydraulics movements

Non marking tires

Open cab

Overhead guard - With tempered glass windshield

Writing table



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes