Technical sheet:

MLT 730-115 V (52)





	MLT 730-115 ∨ (S2) Created on October 16, 2025 at 7:48	} PM ∪
Capacities	Metric	
Max. capacity	Q 3000 kg	
Max. lifting height	h3 6.87 m	
Maximum outreach	4.35 m	
Reach at max. height	1.40 m	
Breakout force with bucket	5056 daN	
Weight and dimensions	JUJU daiv	
Unladen weight (with forks)	7100 kg	
Ground clearance	m4 0.39 m	
Wheelbase	y 2.69 m	
Overall length to carriage (with hitch)	l11 5.16 m	
Front overhang	1.62 m	
Overall width	b1 2.13 m	
Overall cab width	b4 0.95 m	
Overall height	h17 2.34 m	
Filt-down angle	a5 133 °	
Filt-up angle	a4 14°	
External turning radius (over tyres)	Wa1 3.68 m	
Standard tires	Alliance - A580 - 405/70 R24 152.	A8
Drive wheels (front / rear)	2/2	
Steering wheels (front / rear)	2/2	
Performances		
Lifting	6.10 s	
Lowering - · ·	5.10 s	
Extension	8.20 s	
Retraction	6.70 s	
Crowd	4.10 s	
Dump	3.30 s	
Engine		
Engine brand	Deutz	
Engine norm	Stage V	
Engine model	TCD 3.6 L4	
Number of cylinders - Capacity of cylinders	4 - 3621 cm³	
Engine power (Hp / kW)	116 Hp / 85 kW	
Max. torque / Engine rotation	460 Nm @1600 rpm	
Drawbar pull (Laden)	5260 daN	
Reversible fan	Standard	
Engine cooling system	4 radiators (water + intercooler + oil +	fuol)
		iuei)
HVO validated (according to EN 15940 standard)	Yes	
Transmission		
Fransmission type	M-Varioshift	
Number of gears (forward / reverse)	2/2	
Max. travel speed (may vary according to applicable regulations)	40 km/h	
Differential lock	Limited slip differential on front a	xle
Parking brake	Manual	
Service brake	Oil-Immersed multi-discs braking on fro	nt axle
Hydraulics		
Hydraulic pump type	Gear pump	
Hydraulic flow - Pressure	106 l/min - 250 bar	
Flow sharing distributor	Option	
Fank capacities	- Chini	
Hydraulic tank capacity	94	
Fuel tank	78	
Diesel Exhaust fluid (AdBlue® type)	13	
Noise and vibration		
Noise at driving position (LpA) tested following NF EN 12053 norm	73 dB	
Vibration on hands/arms	< 2.50 m/s²	
Miscellaneous		
	Tractor homologation	
Tractor homologation Cab certification	Tractor homologation Cabin ROPS - FOPS level 2	

Optional tires tab

	Overall height	Overall width
ALLIANCE - A580 - 400/70 R20 149A8	2.29 m	2.06 m
ALLIANCE - A580 - 460/70 R24 159A8	2.37 m	2.16 m
NOKIAN - TRI STEEL - 460/65 R24 156A8	2.35 m	2.15 m
MICHELIN - BIBLOAD - 400/70 R20 149A8	2.33 m	2.06 m
MICHELIN - BIBLOAD - 460/70 R24 159A8	2.37 m	2.16 m
MICHELIN - XMCL - 400/70 R20 149A8	2.28 m	2.06 m
MICHELIN - XMCL - 460/70 R24 159A8	2.37 m	2.16 m
TRELLEBORG - TH400 - 460/70 R24 159A8	2.37 m	2.16 m
VREDESTEIN - ENDURION - 460/70 R24 159A8	2.37 m	2.17 m


Options / Finishing


S: Standard / O: Optional / -: Not available

	Classic	Premium	Elite	Platinum
Lifting function				
Attachment hydraulic locking	0	0	0	S
Intelligent hydraulics	0	0	0	S
Operator station				
Air suspension fabric seat - GRAMMER	0	S	-	-
Automatic air conditioning	0	S	S	S
Automatic wheel alignment	0	0	S	S
Bluetooth USB radio - With extra microphone - 100W	0	0	S	S
Bluetooth USB radio - With integrated microphone - 100W	0	S	-	-
Boom suspension - "Active CRC"	0	0	S	S
Exterior right electric rear-view mirror with de-icing	0	0	S	S
Extra front wiper	0	S	S	S
HighView camera on boom head (telescopic part)	0	0	0	S
Low frequency air suspension fabric seat - GRAMMER	0	0	S	-
Low frequency air suspension fabric seat with heating - GRAMMER	0	0	0	S
Mechanical suspension fabric seat - GRAMMER	S	-	-	-
SafeView camera pack - Right hand side and rear (x2)	0	0	0	S
Storage box - On the shelf	0	0	0	S
Tuner car radio - 50W	S	-	-	-
Vision screen - 7 in.	S	S	S	S
Motorization/Power				
Auto reversing fan	S	S	S	S
Continuous flow hydraulics	0	0	S	S
Hand throttle	0	0	S	S
Simultaneous movements flow sharing distributor	0	0	0	S
Secondary functions				
Automatic greasing system (AGS) - Chassis + boom	0	0	0	S
Lighting				
LED+ side work lights (x4)	0	0	0	S
led front road lights	0	0	0	S
LED work lights - On the top of the boom (fixed part) (x2)	0	0	0	S

MLT 730-115 V (S2) - Dimensional drawing








MLT 730-115 V (S2) - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes