

Technical sheet :

MLT 937-115 (S1)



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric	
Max. capacity	Q	3700 kg	
Max. lifting height	h3	9.10 m	
Maximum outreach		6.55 m	
Reach at max. height		2.20 m	
Breakout force with bucket		4472 daN	
Weight and dimensions			
Unladen weight (with forks)		8235 kg	
Ground clearance	m4	0.44 m	
Wheelbase	y	2.81 m	
Overall length to carriage (with hitch)	l11	5.12 m	
Front overhang		1.36 m	
Overall width	b1	2.39 m	
Overall cab width	b4	0.95 m	
Overall height	h17	2.38 m	
Tilt-down angle	a5	133 °	
Tilt-up angle	a4	14 °	
External turning radius (over tyres)	Wa1	3.93 m	
Standard tires	Alliance - A580 - 460/70 R24 159A8		
Drive wheels (front / rear)	2 / 2		
Steering mode	Manicrab, 2 wheel steer, 4 wheel steer, Crab mode		
Performances			
Lifting		7.75 s	
Lowering		7.43 s	
Extension		10.91 s	
Retraction		9.63 s	
Crowd		3.68 s	
Dump		3.12 s	
Engine			
Engine brand		Deutz	
Engine norm		Stage V	
Engine model		TCD 3.6 L4	
Number of cylinders - Capacity of cylinders		4 - 3621 cm³	
Engine power (Hp / kW)		116 Hp / 85 kW	
Max. torque / Engine rotation		460 Nm @1600 rpm	
Drawbar pull (Laden)		8400 daN	
Reversible fan		Option	
Engine cooling system		4 radiators (water + intercooler + hydraulic oil + transmission oil)	
HVO validated (according to EN 15940 standard)		Yes	
Transmission			
Transmission type		Torque converter	
Gearbox		Powershuttle	
Number of gears (forward / reverse)		4 / 4	
Max. travel speed (may vary according to applicable regulations)		33 km/h	
Differential lock		Limited slip differential on front axle	
Parking brake		Automatic negative parking brake	
Service brake		Oil-immersed multi-discs braking on front & rear axles	
Hydraulics			
Hydraulic pump type		Variable displacement pump	
Hydraulic flow - Pressure		150 l/min - 270 bar	
Flow sharing distributor		Standard	
Tank capacities			
Hydraulic tank capacity		135 l	
Fuel		120 l	
Diesel Exhaust fluid (AdBlue® type)		10 l	
Noise and vibration			
Noise at driving position (LpA) tested following NF EN 12053 norm		75 dB	
Vibration on hands/arms		2.50 m/s²	
Miscellaneous			
Tractor homologation		Tractor homologation	
Cab certification		Cabin ROPS - FOPS level 2	
Controls		JSM	

Optional tires tab



	Overall height	Overall width
TRELLEBORG - TH400 - 460/70 R24 159A8	2.37 m	2.40 m
TRELLEBORG - TH400 - 500/70 R24 164A8	2.39 m	2.42 m
MICHELIN - XMCL - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - BIBLOAD - 460/70 R24 159A8	2.37 m	2.40 m
MICHELIN - BIBLOAD - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - XHA - 15.5 R25 158A2	2.37 m	2.40 m
NOKIAN - TRI STEEL - 460/65 R24 156A8	2.36 m	2.40 m
MICHELIN - XMCL - 460/70 R24 159A8	2.37 m	2.40 m
VREDESTEIN - ENDURION - 460/70 R24 159A8	2.38 m	2.41 m
VREDESTEIN - ENDURION - 500/70 R24 164A8	2.41 m	2.44 m
TRELLEBORG - TH500 - 460/70 R24 159A8	2.37 m	2.40 m
ALLIANCE - A585 - 460/70 R24 159A8	2.37 m	2.40 m

Options / Finishing

S : Standard / O : Optional / - : Not available


	Classic	Premium
Lifting function		
Attachment hydraulic locking	O	O
Operator station		
Air suspension fabric seat - GRAMMER	O	S
Automatic air conditioning	O	S
Bluetooth USB radio - With extra microphone - 100W	O	O
Bluetooth USB radio - With integrated microphone - 100W	O	S
Boom suspension - "Active CRC"	O	O
Extra front wiper	O	S
Harmony screen - 5 in.	S	S
Lateral wiper	O	O
Low frequency air suspension fabric seat - GRAMMER	O	O
Low frequency air suspension fabric seat with heating - GRAMMER	O	O
Mechanical suspension fabric seat - GRAMMER	S	-
Storage box - On the shelf	O	O
Tuner car radio - 50W	S	-
Motorization/Power		
Auto reversing fan	O	O
Continuous flow hydraulics	O	O
Secondary functions		
Automatic greasing system (AGS) - Chassis + boom	O	O
Lighting		
led front road lights	O	O
LED work lights - On the top of the boom (fixed part) (x2)	O	O

MLT 937-115 (S1) - Dimensional drawing





MLT 937-115 (S1) - Load chart

Machine on tires with forks Metric



Machine on tires with forks LC 600 mm Metric





Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes