Technical sheet:

MT 625 E







	MT 625 E Created on December 15, 2025 at 8:55 AM
Capacities	Metric
Max. capacity	2500 kg
Max. lifting height	5.85 m
Maximum outreach	3.36 m
Breakout force with bucket	3770 daN
Weight and dimensions	
Overall length to carriage	I11 3.83 m
Overall length (with forks)	l1 5.09 m
Overall width	b1 1.81 m
Overall height	h17 1.92 m
Wheelbase	y 2.30 m
Ground clearance	m4 0.33 m
Overall cab width	b4 0.80 m
Tilt-top angle	
Tilt-down angle	a5 117°
External turning radius (over tyres)	Wa1 3.31 m
Overall weight	4755 kg
Tires type	Inflatable
Standard tires	CAMSO SKS532 12-16.5
Forks length / width / section	l / e / s
Performances	
Lifting	11.10 s
Lowering	8 s
Extension	7.70 s
Retraction	7.40 s
Crowd	4.45 s
Dump	4.30 s
Engine	
Max. torque	200 Nm
Drawbar pull (Laden)	2090 daN
Engine/Battery	
Drive motor power rating	40 kW
Hydraulic motor power	33 kW
Battery technology	Lithium-ion
Battery capacity	348 Ah
Battery energy	35 kWh
Charger Power / Phase / Current type	3 kW / Single-phase / AC
Electric circuit	VKH / Giligie phase / 760
Battery voltage / capacity	100 V / 348 Ah
12V Battery capacity	74 Ah
Transmission	74 All
	Floatical
Transmission type	Electrical
Number of gears (forward / reverse)	1/1
Max. travel speed	20 km/h
Parking brake	Hydraulic spring release SAHR
Service brake	Hydraulic
Hydraulics	
Hydraulic pump type	Gear pump
Hydraulic flow / Pressure	84 I/min-235 bar
Tank capacities	
Hydraulic oil	80 I
Noise and vibration	
Noise at driving position (LpA)	72 dB
Noise to environment (LwA)	92 dB
Vibration on hands/arms	2.50 m/s²
Miscellaneous	
Steering wheels (front / rear)	2/2
Drive wheels (front / rear)	2/2

Options / Finishing


S: Standard / O: Optional / -: Not available


_	
Onboard charger - 3kW AC_MT	
Operator station	
12Volt Power Port	
Adjustable and telescopic steering column	
Air suspension fabric seat - GRAMMER	
Document holder	
Heating	
Manual air conditioning	
Phone support	
Rear window with de-icing	
Rear wiper	
Roof wiper	
Tuner car radio - 50W	
Motorization/Power	
On-board charger 9kW	
Lighting	
Flat Led Rotating Beacon	
led front road lights	
LED front work lights on cab (x2)	
LED rear work lights on cab (x2)	
Security	
Audio warning on reverse	
Battery cut-off	
Speed limiter	
Windscreen sun visor	

Standard	
\$	
S	
S	
0	
0	
\$	
0	
0	
0	
S	
S	
0	
0	
0	
S	
\$	
S	
S	
S	
0	
S	

MT 625 e - Dimensional drawing








MT 625 e - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes