Technical sheet:

# MLT 738-130 PS+ (S1)





Capacities		Metric
Max. capacity	Q	3800 kg
Max. lifting height	h3	6.91 m
faximum outreach		3.98 m
leach at max. height		1 m
dreakout force with bucket		6095 daN
Veight and dimensions		
nladen weight (with forks)		7510 kg
round clearance	m4	0.41 m
/heelbase	У	2.81 m
verall length to carriage (with hitch)	l11	5.03 m
ront overhang		1.27 m
verall width	b1	2.39 m
Iverall cab width	b4	0.95 m
verall height	h17	2.38 m
ilt-down angle	a5	133 °
ilt-up angle	a4	14 °
xternal turning radius (over tyres)	Wa1	3.93 m
tandard tires		Alliance - A580 - 460/70 R24 159A8
rive wheels (front / rear)		2 / 2
teering mode		Manicrab, 2 wheel steer, 4 wheel steer, Crab mo
Performances		
ifting		7.30 s
owering		5.50 s
xtension		6.30 s
etraction		5.70 s
Crowd		3.60 s
Dump		3.10 s
ingine		
ingine brand		Deutz
ingine norm		Stage V
ingine model		TCD 3.6 L4
lumber of cylinders - Capacity of cylinders		4 - 3621 cm³
ingine power (Hp / kW)		129 Hp / 95 kW
		· ·
Max. torque / Engine rotation		500 Nm @1600 rpm
Orawbar pull (Laden)		8000 daN
leversible fan		Standard
ingine cooling system		4 radiators (water + intercooler + hydraulic oil +
		transmission oil)
IVO validated (according to EN 15940 standard)		Yes
ransmission		
ransmission type		Torque converter
earbox		Powershift
lumber of gears (forward / reverse)		6/3
flax. travel speed (may vary according to applicable regulations)		40 km/h
ifferential lock		Limited slip differential on front axle
arking brake		Automatic negative parking brake
aiking blake		
ervice brake		Oil-immersed multi-discs braking on front & rea axles
lydraulics		
lydraulic pump type		Variable displacement pump
ydraulic flow - Pressure		150 l/min - 270 bar
low sharing distributor		Standard
ank capacities		
ydraulic tank capacity		135
uel		120 l
Diesel Exhaust fluid (AdBlue® type)		10
loise and vibration		
loise at driving position (LpA) tested following NF EN 12053 norm		72 dB
fibration on hands/arms		2.50 m/s²
Aiscellaneous		2.30 11/13
		Tractor hamala sation
ractor homologation		Tractor homologation
Cab certification		Cabin ROPS - FOPS level 2 JSM
Controls		

## **Optional tires tab**

	Overall height	Overall width
ALLIANCE - A585 - 460/70 R24 159A8	2.37 m	2.40 m
NOKIAN - TRI STEEL - 460/65 R24 156A8	2.36 m	2.40 m
MICHELIN - BIBLOAD - 460/70 R24 159A8	2.37 m	2.40 m
MICHELIN - BIBLOAD - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - XMCL - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - XHA - 15.5 R25 158A2	2.37 m	2.40 m
MICHELIN - XMCL - 460/70 R24 159A8	2.37 m	2.40 m
TRELLEBORG - TH400 - 460/70 R24 159A8	2.37 m	2.40 m
TRELLEBORG - TH400 - 500/70 R24 164A8	2.39 m	2.42 m
TRELLEBORG - TH500 - 460/70 R24 159A8	2.37 m	2.40 m
VREDESTEIN - ENDURION - 460/70 R24 159A8	2.38 m	2.41 m
VREDESTEIN - ENDURION - 500/70 R24 164A8	2.41 m	2.44 m


### **Options / Finishing**


S : Standard / O : Optional / - : Not available

	Classic	Premium	Elite	Platinum
Lifting function				
Attachment hydraulic locking	0	0	0	S
Intelligent hydraulics	0	0	0	S
Regenerative Hydraulics	0	0	0	S
Operator station				
Air suspension fabric seat - GRAMMER	0	S	-	-
Automatic air conditioning	0	S	S	S
Automatic wheel alignment	0	0	S	S
Bluetooth USB radio - With extra microphone - 100W	0	0	S	S
Bluetooth USB radio - With integrated microphone - 100W	0	S	-	-
Boom suspension - "Active CRC"	0	0	S	S
Exterior right electric rear-view mirror with de-icing	0	0	S	S
Extra front wiper	0	S	S	S
HighView camera on boom head (telescopic part)	0	0	0	S
Lateral wiper	S	S	S	S
Low frequency air suspension fabric seat - GRAMMER	0	0	S	-
Low frequency air suspension fabric seat with heating - GRAMMER	0	0	0	S
Mechanical suspension fabric seat - GRAMMER	S	•	-	-
SafeView camera pack - Right hand side and rear (x2)	0	0	0	S
Storage box - On the shelf	0	0	0	S
Tuner car radio - 50W	S	-	-	-
Vision screen - 7 in.	S	S	S	S
Motorization/Power				
Auto reversing fan	S	S	S	S
Continuous flow hydraulics	0	0	S	S
Hand throttle	0	0	S	S
Secondary functions				
Automatic greasing system (AGS) - Chassis + boom	0	0	0	S
Lighting				
LED+ side work lights (x4)	0	0	0	S
led front road lights	0	0	0	S
LED work lights - On the top of the boom (fixed part) (x2)	0	0	0	S

#### MLT 738-130 PS+ (S1) - Dimensional drawing








MLT 738-130 PS+ (S1) - Load chart

Machine on tires with forks Metric







#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes