Technical sheet:

MLT 742-140 V+ (51)





	MLT 742-140 V+ (S1) Created on November 30, 2025 at 4:37 AM
Capacities	Metric
Max. capacity	Q 4200 kg
Max. lifting height	h3 6.91 m
Maximum outreach	3.96 m
Reach at max. height	1 m
Breakout force with bucket	5748 daN
Weight and dimensions	57 10 dd.ii
Unladen weight (with forks)	7950 kg
Ground clearance	m4 0.42 m
Wheelbase	y 2.81 m
Overall length to carriage (with hitch)	l11 5.02 m
Front overhang	1.26 m
Overall width	
Overall cab width	b4 0.95 m
Overall height	h17 2.38 m
Tilt-down angle	a5 133 °
Tilt-up angle	a4 14 °
External turning radius (over tyres)	Wa1 3.93 m
Standard tires	Alliance - A580 - 460/70 R24 159A8
Drive wheels (front / rear)	2/2
Steering mode	Manicrab, 2 wheel steer, 4 wheel steer, Crab m
Performances	
Lifting	8.10 s
Lowering	8.50 s
Extension	6.90 s
Retraction	6 s
Crowd	3.80 s
Dump	3.30 s
Engine	3.30 \$
	Doub
Engine brand	Deutz
Engine norm	Stage V
Engine model	TCD 3.6 L4
Number of cylinders - Capacity of cylinders	4 - 3621 cm³
Engine power (Hp / kW)	136 Hp / 100 kW
Max. torque / Engine rotation	500 Nm @1600 rpm
Drawbar pull (Laden)	6450 daN
Reversible fan	Standard
Engine cooling system	Engine cooling system - 4 radiators (water + intercooler + hydraulic oil + hydraulic oil for transmission)
HVO validated (according to EN 15940 standard)	Yes
Transmission	
Transmission type	M-Vario Plus
Max. travel speed (may vary according to applicable regulations)	40 km/h
Differential lock	
	Limited slip differential on front axle
Parking brake	Automatic negative parking brake
Service brake	Oil-immersed multi-discs braking on front & re axles
Hydraulics	
Hydraulic pump type	Variable displacement pump
Hydraulic flow - Pressure	170 l/min - 270 bar
Flow sharing distributor	Standard
Tank capacities	
Hydraulic tank capacity	135
Fuel	120
Diesel Exhaust fluid (AdBlue® type)	101
Noise and vibration	
Noise at driving position (LpA) tested following NF EN 12053 norm	72 dB
Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	< 2.30 III/5-
	T. A. A. A. A.
Tractor homologation	Tractor homologation
Cab certification	Cabin ROPS - FOPS level 2
Controls	JSM

Optional tires tab

	Overall height	Overall width
ALLIANCE - A585 - 460/70 R24 159A8	2.37 m	2.40 m
NOKIAN - TRI STEEL - 460/65 R24 156A8	2.36 m	2.40 m
MICHELIN - XMCL - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - BIBLOAD - 460/70 R24 159A8	2.37 m	2.40 m
MICHELIN - BIBLOAD - 500/70 R24 164A8	2.39 m	2.43 m
MICHELIN - XHA - 15.5 R25 158A2	2.37 m	2.40 m
MICHELIN - XMCL - 460/70 R24 159A8	2.37 m	2.40 m
TRELLEBORG - TH400 - 460/70 R24 159A8	2.37 m	2.40 m
TRELLEBORG - TH400 - 500/70 R24 164A8	2.39 m	2.42 m
TRELLEBORG - TH500 - 460/70 R24 159A8	2.37 m	2.40 m
VREDESTEIN - ENDURION - 460/70 R24 159A8	2.38 m	2.41 m
VREDESTEIN - ENDURION - 500/70 R24 164A8	2.41 m	2.44 m


Options / Finishing


S : Standard / O : Optional / - : Not available

	Classic	Premium	Elite	Platinum
Lifting function				
Attachment hydraulic locking	0	0	0	S
Intelligent hydraulics	0	0	S	S
Regenerative Hydraulics	0	S	S	S
Operator station				
Air suspension fabric seat - GRAMMER	0	S	-	-
Automatic air conditioning	0	S	S	S
Automatic wheel alignment	0	0	S	S
Bluetooth USB radio - With extra microphone - 100W	0	0	S	S
Bluetooth USB radio - With integrated microphone - 100W	0	S	-	-
Boom suspension - "Active CRC"	0	0	S	S
Exterior right electric rear-view mirror with de-icing	0	0	S	S
Extra front wiper	0	S	S	S
HighView camera on boom head (telescopic part)	0	0	0	S
Lateral wiper	S	S	S	S
Low frequency air suspension fabric seat - GRAMMER	0	0	S	-
Low frequency air suspension fabric seat with heating - GRAMMER	0	0	0	S
Mechanical suspension fabric seat - GRAMMER	S	-	-	-
SafeView camera pack - Right hand side and rear (x2)	0	0	0	S
Storage box - On the shelf	0	0	0	S
Tuner car radio - 50W	S	-	-	-
Vision screen - 7 in.	S	S	S	S
Motorization/Power				
Auto reversing fan	S	S	S	S
Continuous flow hydraulics	0	0	S	S
Hand throttle	S	S	S	S
Secondary functions				
Automatic greasing system (AGS) - Chassis + boom	0	0	0	S
Lighting				
LED+ side work lights (x4)	0	0	0	S
led front road lights	0	0	0	S
LED work lights - On the top of the boom (fixed part) (x2)	0	0	0	S

MLT 742-140 V+ (S1) - Dimensional drawing








MLT 742-140 V+ (S1) - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes