

Technical sheet :

# MLT 625 E

OXYGEN




 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric	
Max. capacity	Q	2500 kg	
Max. lifting height	h3	5.90 m	
Maximum outreach		3.30 m	
Reach at max. height		0.50 m	
Breakout force with bucket		3770 daN	
Weight and dimensions			
Unladen weight (with forks)		4762 kg	
Ground clearance	m4	0.38 m	
Wheelbase	y	2.30 m	
Overall length to carriage (with hitch)	l11	3.90 m	
Overall length to carriage (without hitch)	l3	3.90 m	
Overall width	b1	1.81 m	
Overall cab width	b4	0.80 m	
Overall height	h17	2 m	
Tilt-down angle	a5	117 °	
Tilt-up angle	a4	12 °	
External turning radius (over tyres)	Wa1	3.31 m	
Standard tires	Alliance - A580 - 300/75 R18 142A8		
Steering mode	Manicrab, 2 wheel steer, 4 wheel steer, Crab mode		
Performances			
Lifting		11.10 s	
Lowering		8 s	
Extension		7.70 s	
Retraction		7.40 s	
Crowd		4.45 s	
Dump		4.30 s	
Engine/Battery			
Battery technology		Lithium-ion	
Battery capacity		348 Ah	
Battery energy		34.80 kWh	
Drive motor power rating		40 kW	
Hydraulic motor power		30 kW	
Charger Power		9 kW	
Electric circuit			
Battery nominal voltage		100 V	
12V Battery capacity		74 Ah	
Transmission			
Transmission type		Electrical	
Number of gears (forward / reverse)		1 / 1	
Max. travel speed (may vary according to applicable regulations)		20 km/h	
Differential lock		Limited slip differential on front axle	
Parking brake		Automatic negative parking brake	
Service brake		Oil-Immersed multi-discs braking on front axles	
Hydraulics			
Hydraulic pump type		Gear pump	
Hydraulic flow - Pressure		84 l/min - 235 bar	
Flow sharing distributor		Standard	
Tank capacities			
Hydraulic tank capacity		80 l	
Noise and vibration			
Noise at driving position (LpA) tested following NF EN 12053 norm		72 dB	
Noise to environment (LwA)		92 dB	
Vibration on hands/arms		2.50 m/s <sup>2</sup>	
Miscellaneous			
Cab certification		ROPS - FOPS cab (level 1)	
Controls		JSM	

## Optional tires tab


MICHELIN - BIBSTEEL ALL TERRAIN - 300/70 R16.5 141A5	Overall height	Overall width
CAMSO - SKS532 - 12-16.5 145A2	1.97 m	1.81 m
CAMSO - SKS732 - 12-16.5 145A2	1.92 m	1.81 m
	1.92 m	1.81 m

## MLT 625 e - Dimensional drawing




## MLT 625 e - Load chart

Machine on tires with forks Metric



Machine on tires with forks LC 600 mm Metric





# **MANITOU** HANDLING YOUR WORLD

## Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes