

Technical sheet :

# ES 316 L EASY

OXYGEN



 **MANITOU**  
HANDLING YOUR WORLD

Technical characteristics			Metric	
1.1	Manufacturer		MANITOU	
1.2	Model Name		ES 316 L Easy	
1.3	Power source		Electrical - Lithium	
1.4	Operator type		Walking alongside	
1.5	Max. capacity	Q	1600 kg	
1.6	Load center of gravity	c	600 mm	
1.8	Load distance, centre of drive axle to fork (low/raised) - Low position / Raised position	x	768 mm / 700 mm	
1.9	Wheelbase	y	1455 mm	
Weight				
2.1	Service weight		1120 kg	
2.2	Weight on front axle (laden) / rear axle (laden)		930 kg / 1790 kg	
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		760 kg / 360 kg	
Wheels				
3.1	Tires type		Polyurethane cushion	
3.3	Number of load wheels / Size of load wheels		4 / 83X73	
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		1 / 140X55	
3.5	Number of front wheels / rear wheels		2 / 4	
3.2	Size of drive wheels		250X80	
3.6	Front wheel gauge	b10	510 mm	
3.7	Rear wheel gauge	b11	385 mm	
Dimensions				
4.10	Height of wheel arms	h8	80 mm	
4.15	Fork height in low position	h13	90 mm	
4.19	Overall length	l1	2000 mm	
4.20	Length to face of forks	l2	850 mm	
4.21	Overall width	b1	800 mm	
4.22	Forks section / width / length	s / e / l	65 mm / 185 mm / 1150 mm	
4.24	Fork carriage width	b3	680 mm	
4.25	Forks spread	b5	570 mm	
4.32	Ground clearance at centre of wheelbase	m2	15 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	2528 mm	
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2474 mm	
4.6	Initial lift	h5	125 mm	
4.35	Turning radius	Wa	1685 mm	
4.9	Height tiller min. / max.	h14	790 mm / 1205 mm	
Performances				
5.1	Travel speed (laden / unladen)		6 km/h / 6 km/h	
5.2	Lifting speed (laden / unladen)		0.18 m/s / 0.40 m/s	
5.3	Lowering speed (laden / unladen)		0.45 m/s / 0.40 m/s	
5.8	Max Gradeability (laden / unladen)		6 % / 16 %	
5.10	Service brake		Electro magnetic	
Engine				
6.1	Drive motor rating S2 60 min		2.20 kW	
6.2	Lift motor rating at S3 15%		4.20 kW	
6.4	Battery voltage / capacity		48 V / 105 Ah	
6.5	Battery technology		Lithium-ion	
6.5	Battery weight (+/- 5%)		65 kg	
6.6.1	Energy consumption according to DIN EN 16796		0.55 kWh/h	

ES 316 L Easy - Dimensional drawing



## Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 29	FVD 35
h1 - Mast lowered height	mm	1990	2290
h2 - Mast free lift	mm	90	90
h3 - Mast lifting height	mm	2900	3500
h4 - Mast extended height	mm	3440	4040
Residual capacity at max height	kg	1200	930
Height at max capacity	mm	2490	2490

Free Lift Triplex (FLT)		FLT 42	FLT 55
h1 - Mast lowered height	mm	1890	2330
h2 - Mast free lift	mm	1390	1830
h3 - Mast lifting height	mm	4200	5500
h4 - Mast extended height	mm	4720	6020
Residual capacity at max height	kg	780	480
Height at max capacity	mm	2490	2490

## Equipment

Standard
Anti-crushing safety device
Battery - 5.04kWh - Lithium-ion
Emergency stop
Onboard charger - 0.96kW AC - Lithium-ion - Single-phase
Pincode - On tiller
Polyurethane tandem-load wheels
Turtle button

Optional
Cold environment (from -28°C (-18°F))
External charger - 2.4kW AC - Lithium-ion - Single-phase
Key switch entry
Soft polyurethane drive wheel - 75 shore



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes