

Ficha técnica :

# **MI 20 GST5 FOB**

---



 **MANITOU**  
HANDLING YOUR WORLD

| Technical characteristics |   | Métrico   |                            |
|---------------------------|---|-----------|----------------------------|
| 1.1                       | Manufacturer  |           | MANITOU                    |
| 1.2                       | Model Name  |           | MI 20 G ST5                |
| 1.3                       | Power source  |           | Lpg                        |
| 1.4                       | Operator type   |           | Seated                     |
| 1.5                       | Max. capacity   | Q         | 2000 kg                    |
| 1.6                       | Load center of gravity  | c         | 500 mm                     |
| 1.8                       | Load distance, centre of drive axle to fork                     | x         | 465 mm                     |
| 1.9                       | Wheelbase   | y         | 1600 mm                    |
|                           | Standard mast reference of the machine                          |           | FVD 33                     |
| Weight                    |   |           |                            |
| 2.1                       | Service weight  |           | 3620 kg                    |
| 2.2                       | Weight on front axle (laden) / rear axle (laden)                |           | 4930 kg / 690 kg           |
| 2.3                       | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 1720 kg / 1900 kg          |
| Wheels                    |   |           |                            |
| 3.1                       | Tires type  |           | Super Elastic              |
| 3.2                       | Dimensions of front wheels                                      |           | 7.00-12 12                 |
| 3.3                       | Dimensions of rear wheels                                       |           | 6.00-9 10                  |
| 3.5                       | Number of front wheels / rear wheels                            |           | 2 / 2                      |
| 3.5.2                     | Number of drive wheels  |           | 2                          |
| 3.6                       | Front wheel gauge   | b10       | 965 mm                     |
| 3.7                       | Rear wheel gauge  | b11       | 973 mm                     |
| Dimensions                |   |           |                            |
| 4.7                       | Height of overhead guard (cabin)                                | h6        | 2115 mm                    |
| 4.8                       | Seat height/stand height  | h7        | 1190 mm                    |
| 4.12                      | Height of towing bar (coupling height)                          | h10       | 355 mm                     |
| 4.19                      | Overall length  | l1        | 3615 mm                    |
| 4.20                      | Length to face of forks   | l2        | 2465 mm                    |
| 4.21                      | Overall width   | b1        | 1155 mm                    |
| 4.21                      | Overall width - Single wheels                                   | b1        | 1155 mm                    |
| 4.21                      | Overall width - Twinned wheels                                  | b1        | 1595 mm                    |
| 4.22                      | Forks section / width / length                                  | s / e / l | 40 mm x 122 mm x 1150 mm   |
| 4.23                      | Fork carriage ISO 2328 (class/form) A/B                         |           | 2A                         |
| 4.24                      | Fork carriage width   | b3        | 1038 mm                    |
| 4.31                      | Ground clearance below mast                                     | m1        | 115 mm                     |
| 4.32                      | Ground clearance at centre of wheelbase                         | m2        | 175 mm                     |
| 4.33                      | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 3865 mm                    |
| 4.34                      | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4065 mm                    |
| 4.35                      | Turning radius  | Wa        | 2200 mm                    |
| 4.36                      | Internal turning radius (over tyres)                            | b13       | 145 mm                     |
| Performances              |   |           |                            |
| 5.1                       | Travel speed (laden / unladen)                                  |           | 18.80 km/h-19.40 km/h      |
| 5.2                       | Lifting speed (laden / unladen)                                 |           | 0.55 m/s-0.64 m/s          |
| 5.3                       | Lowering speed (laden / unladen)                                |           | 0.48 m/s-0.50 m/s          |
| 5.5                       | Drawbar pull (Laden / Unladen)                                  |           | 1940 daN / 1040 daN        |
| 5.7                       | Gradeability (laden / unladen)                                  |           | 20 % / 20 %                |
| 5.10                      | Service brake   |           | Hydraulic                  |
| Engine                    |   |           |                            |
| 7.1                       | Engine brand / model  |           | GCT (ex-Nissan) / GK25 LPG |
| 7.2                       | I.C. Engine power rating  |           | 43.40 kW                   |
| 7.3                       | Rated speed   |           | 2700 rpm                   |
| 7.4                       | Number of cylinders / Capacity of cylinders                     |           | 4 - 2488 cm³               |
| Miscellaneous             |   |           |                            |
| 8.2                       | Working hydraulic pressure for attachments                      |           | 160 bar                    |
| 8.3                       | Oil flow rate for attachments                                   |           | 35 l/min                   |
| 8.4                       | Measured/guaranteed mean noise level at the ear of the operator |           | < 80 dB                    |

MI 20 G ST5 FOB - Diagrama dimensional







 **MANITOU**  
**HANDLING YOUR WORLD**

**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes