

Technical sheet :


MI 80 D ST5



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics			Metric
1.1	Manufacturer		MANITOU
1.2	Model Name		MI 80 D ST5
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	8000 kg
1.6	Load center of gravity	c	600 mm
1.8	Load distance, centre of drive axle to fork	x	714 mm
1.9	Wheelbase	y	2600 mm
	Standard mast reference of the machine		FVD 30
Weight			
2.1	Service weight		12540 kg
2.2	Weight on front axle (laden) / rear axle (laden)		18340 kg / 2200 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		5180 kg / 7360 kg
Wheels			
3.1	Tires type		Pneumatic
3.2	Dimensions of front wheels		9.00-20-14PR
3.3	Dimensions of rear wheels		9.00-20-14PR
3.5	Number of front wheels / rear wheels		4 / 2
3.5.2	Number of drive wheels		4
3.6	Front wheel gauge	b10	1628 mm
3.7	Rear wheel gauge	b11	1700 mm
Dimensions			
4.8	Seat height/stand height	h7	1350 mm
4.7	Height of overhead guard (cabin)	h6	2580 mm
4.12	Height of towing bar (coupling height)	h10	505 mm
4.19	Overall length	l1	5524 mm
4.20	Length to face of forks	l2	4004 mm
4.21	Overall width	b1	2165 mm
4.21	Overall width - Twinned wheels	b1	2165 mm
4.22	Forks section / width / length	s / e / l	75 mm x 160 mm x 1520 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		4A
4.24	Fork carriage width	b3	2100 mm
4.31	Ground clearance below mast	m1	250 mm
4.32	Ground clearance at centre of wheelbase	m2	339 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	5644 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	5844 mm
4.35	Turning radius	Wa	3730 mm
4.36	Internal turning radius (over tyres)	b13	1327 mm
Performances			
5.1	Travel speed (laden / unladen)		26 km/h-27 km/h
5.2	Lifting speed (laden / unladen)		0.38 m/s-0.40 m/s
5.3	Lowering speed (laden / unladen)		0.43 m/s-0.39 m/s
5.5	Drawbar pull (Laden / Unladen)		6500 daN / 4500 daN
5.7	Gradeability (laden / unladen)		35 % / 35 %
5.10	Service brake		Hydraulic
Engine			
7.1	Engine brand / model / nom		Deutz / TCD 3.6 / Stage V
7.2	Engine power (Hp / kW)		116 Hp/85 kW
7.3	Rated speed		2200 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 3600 cm³
Miscellaneous			
8.2	Working hydraulic pressure for attachments		195 bar
8.3	Oil flow rate for attachments		55 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 84 dB

MI 80 D ST5 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)	FVD 30	FVD 33	FVD 36	FVD 40	FVD 45	FVD 50
α - Mast/fork carriage tilt, forward	6.20	6.20	6.20	6.20	6.20	6.20
β - Mast/fork carriage tilt, backward	12.20	12.20	12.20	12.20	6.20	6.20
h1 - Mast lowered height	2700	2850	3000	3200	3500	3750
h2 - Mast free lift	200	200	200	200	200	200
h3 - Mast lifting height	3000	3300	3600	4000	4500	5000
h4 - Mast extended height	4210	4510	4810	5210	5710	6210
Residual capacity at max height	8000	8000	8000	8000	8000	8000
Height at max capacity	3000	3300	3600	4000	4500	5000
Height at max capacity with integrated sideshift	3000	3300	3600	4000	4500	5000

Free Lift Triplex (FLT)	FLT 45	FLT 48	FLT 50	FLT 55	FLT 60
α - Mast/fork carriage tilt, forward	6.20	6.20	6.20	3.20	3.20
β - Mast/fork carriage tilt, backward	6.20	6.20	6.20	6.20	6.20
h1 - Mast lowered height	2750	2850	2950	3100	3250
h2 - Mast free lift	1485	1585	1600	1800	1985
h3 - Mast lifting height	4500	4800	5000	5500	6000
h4 - Mast extended height	5775	6075	6360	6810	7275
Residual capacity at max height	7000	7000	6500	6100	5600
Height at max capacity	4500	4800	5000	5500	6000
Height at max capacity with integrated sideshift	4500	4800	5000	5500	6000



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes