

Fiche technique :

MI 50 LD ST5 FOB



 **MANITOU**
HANDLING YOUR WORLD

| Technical characteristics | | | Métrique |
|---------------------------|---|-----------|--------------------------|
| 1.1 | Manufacturer | | MANITOU |
| 1.2 | Model Name | | MI 50 LD FOB |
| 1.3 | Power source | | Diesel |
| 1.4 | Operator type | | Seated |
| 1.5 | Max. capacity | Q | 5000 kg |
| 1.6 | Load center of gravity | c | 600 mm |
| 1.8 | Load distance, centre of drive axle to fork | x | 598 mm |
| 1.9 | Wheelbase | y | 2300 mm |
| | Standard mast reference of the machine | | FVD 30 |
| Weight | | | |
| 2.1 | Service weight | | 8810 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 12250 kg / 1560 kg |
| Wheels | | | |
| 3.1 | Tires type | | Super Elastic |
| 3.2 | Dimensions of front wheels | | 8.25-15 14PR |
| 3.3 | Dimensions of rear wheels | | 8.25-15 14PR |
| 3.5 | Number of front wheels / rear wheels | | 4 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 1489 mm |
| 3.7 | Rear wheel gauge | b11 | 1700 mm |
| Dimensions | | | |
| 4.7 | Height of overhead guard (cabin) | h6 | 2430 mm |
| 4.8 | Seat height/stand height | h7 | 1350 mm |
| 4.12 | Height of towing bar (coupling height) | h10 | 710 mm |
| 4.19 | Overall length | l1 | 4719 mm |
| 4.20 | Length to face of forks | l2 | 3499 mm |
| 4.21 | Overall width | b1 | 1990 mm |
| 4.21 | Overall width - Twinned wheels | b1 | 1990 mm |
| 4.22 | Forks section / width / length | s / e / l | 60 mm x 150 mm x 1220 mm |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | 4A |
| 4.31 | Ground clearance below mast | m1 | 190 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 270 mm |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 5230 mm |
| 4.36 | Internal turning radius (over tyres) | b13 | 110 mm |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 23 km/h-24 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 0.38 m/s-0.46 m/s |
| 5.3 | Lowering speed (laden / unladen) | | 0.48 m/s-0.42 m/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 6400 daN / 2540 daN |
| 5.7 | Gradeability (laden / unladen) | | 20 % / 20 % |
| 5.10 | Service brake | | Hydraulic |
| Engine | | | |
| 7.1 | Engine brand / model | | Deutz / TCD 3.6 L4 |
| 7.2 | I.C. Engine power rating | | 55.40 kW |
| 7.3 | Rated speed | | 2300 rpm |
| 7.4 | Number of cylinders / Capacity of cylinders | | 4 - 3621 cm³ |
| Miscellaneous | | | |
| 8.3 | Oil flow rate for attachments | | 165 l/min |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 84 dB |

MI 50 LD ST5 FOB - Schémas d'encombrement



Caractéristiques des mâts et capacités résiduelles

| Full Visibility Duplex (FVD) | FVD 30 | FVD 33 | FVD 36 | FVD 40 | FVD 45 | FVD 50 |
|---|--------|--------|--------|--------|--------|--------|
| α - Mast/fork carriage tilt, forward | ° | 6 | 6 | 6 | 6 | 6 |
| β - Mast/fork carriage tilt, backward | ° | 12 | 12 | 12 | 12 | 6 |
| h1 - Mast lowered height | mm | 2500 | 2650 | 2800 | 3000 | 3550 |
| h2 - Mast free lift | mm | 160 | 160 | 160 | 160 | 160 |
| h3 - Mast lifting height | mm | 3000 | 3300 | 3600 | 4000 | 5000 |
| h4 - Mast extended height | mm | 3995 | 4295 | 4595 | 4995 | 6000 |
| Residual capacity at max height | kg | 5000 | 5000 | 5000 | 5000 | 5000 |
| Residual capacity with hooked-on side shift at max height | kg | 4500 | 4500 | 4500 | 4500 | 4500 |
| Height at max capacity | mm | 3000 | 3300 | 3600 | 4000 | 5000 |
| Height at max capacity with hooked-on sideshift | mm | 3000 | 3300 | 3600 | 4000 | 5000 |

| Free Lift Duplex (FLD) | FLD 30 | FLD 33 | FLD 36 | FLD 40 |
|---|--------|--------|--------|--------|
| α - Mast/fork carriage tilt, forward | ° | 6 | 6 | 6 |
| β - Mast/fork carriage tilt, backward | ° | 12 | 12 | 12 |
| h1 - Mast lowered height | mm | 2450 | 2600 | 2750 |
| h2 - Mast free lift | mm | 1495 | 1645 | 1795 |
| h3 - Mast lifting height | mm | 3000 | 3300 | 3600 |
| h4 - Mast extended height | mm | 3955 | 4255 | 4555 |
| Residual capacity at max height | kg | 5000 | 5000 | 5000 |
| Residual capacity with hooked-on side shift at max height | kg | 4500 | 4500 | 4500 |
| Height at max capacity | mm | 3000 | 3300 | 3600 |
| Height at max capacity with hooked-on sideshift | mm | 3000 | 3300 | 3600 |

| Free Lift Triplex (FLT) | FLT 45 | FLT 48 | FLT 50 | FLT 55 | FLT 60 |
|---|--------|--------|--------|--------|--------|
| α - Mast/fork carriage tilt, forward | ° | 6 | 6 | 3 | 3 |
| β - Mast/fork carriage tilt, backward | ° | 6 | 6 | 6 | 6 |
| h1 - Mast lowered height | mm | 2725 | 2825 | 2875 | 3075 |
| h2 - Mast free lift | mm | 1500 | 1600 | 1672 | 1800 |
| h3 - Mast lifting height | mm | 4500 | 4800 | 5000 | 5500 |
| h4 - Mast extended height | mm | 5735 | 6035 | 6213 | 6785 |
| Residual capacity at max height | kg | 4500 | 4500 | 4500 | 4200 |
| Residual capacity with hooked-on side shift at max height | kg | 4000 | 4000 | 4000 | 3700 |
| Height at max capacity | mm | 4500 | 4800 | 5000 | 5500 |
| Height at max capacity with hooked-on sideshift | mm | 4500 | 4800 | 5000 | 5500 |



Siège Social

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



Cette publication présente le descriptif des versions et possibilités de configuration des produits Manitou qui peuvent différer en équipement. Les équipements présentés dans cette brochure peuvent être de série, en option, ou non disponibles suivant les versions. Manitou se réserve le droit, à tout moment et sans préavis, de modifier les spécifications décrites et représentées. Les spécifications portées n'engagent pas le constructeur. Pour plus de détails, contactez votre concessionnaire Manitou. Document non contractuel. Présentation des produits non contractuelle. Liste des spécifications non exhaustive. Les logos ainsi que l'identité visuelle de l'entreprise sont la propriété de Manitou et ne peuvent être utilisés sans autorisation. Tous droits réservés. Les photos et schémas contenus dans la présente brochure ne sont fournis qu'à des fins de consultation et à titre indicatif.

Manitou BF SA - Société anonyme à conseil d'administration - Capital social : 39 668 399 euros - 857 802 508 RCS Nantes