

AL320

ARTICULATED LOADERS



Key Features

- ✓ 4-Post Open Canopy ROPS and FOPS Certified
- ✓ Front Auxiliary Hydraulics with Flat-Faced Couplers
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Automotive Style Hydrostatic Drive, 2-Speed
- ✓ Perkins Diesel Engine
- ✓ Deluxe, Tilttable Steering Column
- ✓ Multi-Function Joystick

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Static tipping load with bucket (straight)	3556 lb	1613 kg
	Static tipping load with bucket (full turn)	3122 lb	1416 kg
	Static tipping load with forks (straight)	2663 lb	1208 kg
	Static tipping load with forks (full turn)	2339 lb	1061 kg
	Max. height of bucket pivot point	8 ft 2 in	2.48 m
Weight and dimensions	Unladen weight (with forks) with 4-post canopy	4630 lb	2100 kg
	Wheelbase	5 ft 5 in	1.65 m
	Overall cab width	3 ft 3 in	0.99 m
	Overall height with 4 posts canopy	7 ft 5 in	2.25 m
	Dump reach - Full height	14 in	344 mm
	Hood Height	4 ft 7 in	1.40 m
	Overall Operating Height - Fully Raised	12 ft 2 in	3.69 m
	Articulation angle	45 °	45 °
	Maximum oscillation angle	11 °	11 °
	Overall length with bucket	13 ft 8 in	4.15 m
	Overall width less bucket	3 ft 7 in	1.10 m
	Overall length - Less Bucket	11 ft 4 in	3.46 m
	Dump angle - Fully raised	39 °	39 °
	Dump Height - Fully Raised	7 ft	2.12 m
	Maximum Rollback Angle - Fully Raised	50 °	50 °
	Digging Position	-3 in	-79 mm
	Ground clearance	13 in	320 mm
	Clearance Radius - Front with Bucket	10 ft 8 in	3.24 m
	Clearance Radius - Less bucket	9 ft 1 in	2.76 m
	Ground Plane to Bucket Edge Height	8 ft 9 in	2.65 m
	Tread width (wheel center)	33 in	836 mm
	Attachment Pivot Clearance	4 in	103 mm
	Height from ground to axle center	8 in	214 mm
	Bucket Width	5 ft	1.52 m
	Front Wheel Center to Pivot Pin	26 in	669 mm
	Height to Hinge Pin - Fully Raised	8 ft 3 in	2.52 m
Engine	Engine brand	Perkins	Perkins
	Engine model	403J-17	403J-17
	Engine norm	Stage V	Stage V
	Number of cylinders	3	3
	I.C. Engine power rating / Power	24.70 Hp / 18.40 kW	24.70 Hp / 18.40 kW
Transmission	Max. torque / Engine rotation	63 ft/lbs / 1800 rpm	85 Nm / 1800 rpm
	Engine cooling system	Water	Water
	Transmission type	Hydrostatic	Hydrostatic
	Number of gears (forward / reverse)	2 / 2	2 / 2
	Max. travel speed (may vary according to applicable regulations)	12 mph	20 km/h
Hydraulics	Parking brake	Mechanical hand-operated parking brake	Mechanical hand-operated parking brake
	Service brake	Hydraulic drum brake on front axle, acting on all 4 wheels	Hydraulic drum brake on front axle, acting on all 4 wheels
	Hydraulic pump type	Gear pump	Gear pump
	Hydraulic flow - Pressure	8 US gpm / 3002 PSI	30 l/min / 207 bar
Tank capacities	Drive hydraulic system pressure	3002 PSI	207 bar
	Hydraulic oil	6 US gal	24 l
	Fuel tank	9 US gal	35 l



STANDARD FEATURES

- Counterweight
- Inching Pedal
- Instrument Panel - Deluxe
- Hydrostatic Drive - Servo
- Tilttable, Deluxe Steering Column
- Adjustable 2-inch Seat Belt
- Lockable Engine Cover and Fuel Cap
- Horn
- Combination Radiator & Hydraulic Oil Cooler
- Adjustable Seat 5-Way
- Additional Set of Front Auxiliary Hydraulics
- Battery Disconnect

OPTIONAL FEATURES

- LED front road lights
- LED Work Lights
- Cabin with Heat
- Air suspension seat

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT