


Technisches Datenblatt :

MI 55 GST5



Technical characteristics			Metrisch	
1.1	Manufacturer		MANITOU	
1.2	Model Name		MI 55 G ST5	
1.3	Power source		Lpg	
1.4	Operator type		Seated	
1.5	Max. capacity	Q	5500 kg	
1.6	Load center of gravity	c	500 mm	
1.8	Load distance, centre of drive axle to fork	x	585 mm	
1.9	Wheelbase	y	2150 mm	
Weight				
2.1	Service weight		7250 kg	
2.2	Weight on front axle (laden) / rear axle (laden)		11000 kg / 1750 kg	
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		3300 kg / 3950 kg	
Wheels				
3.1	Tires type		Super Elastic	
3.2	Dimensions of front wheels		300-15 18PR	
3.3	Dimensions of rear wheels		7.00-12 12PR	
3.5	Number of front wheels / rear wheels		2 / 2	
3.5.2	Number of drive wheels		2	
3.6	Front wheel gauge	b10	1190 mm	
3.7	Rear wheel gauge	b11	1130 mm	
Dimensions				
4.7	Height of overhead guard (cabin)	h6	2390 mm	
4.8	Seat height/stand height	h7	1370 mm	
4.12	Height of towing bar (coupling height)	h10	445 mm	
4.19	Overall length	l1	4550 mm	
4.20	Length to face of forks	l2	3330 mm	
4.21	Overall width	b1	1490 mm	
4.21	Overall width - Single wheels	b1	1490 mm	
4.21	Overall width - Twinned wheels	b1	1940 mm	
4.22	Forks section / width / length	s / e / l	60 mm x 150 mm x 1220 mm	
4.23	Fork carriage ISO 2328 (class/form) A/B		4A	
4.24	Fork carriage width	b3	1250 mm	
4.31	Ground clearance below mast	m1	170 mm	
4.32	Ground clearance at centre of wheelbase	m2	230 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4755 mm	
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4555 mm	
4.35	Turning radius	Wa	2970 mm	
4.36	Internal turning radius (over tyres)	b13	130 mm	
Performances				
5.1	Travel speed (laden / unladen)		21 km/h-22 km/h	
5.2	Lifting speed (laden / unladen)		0.43 m/s-0.46 m/s	
5.3	Lowering speed (laden / unladen)		0.50 m/s-0.50 m/s	
5.7	Gradeability (laden / unladen)		20 % / 20 %	
5.10	Service brake		Hydraulic	
Engine				
7.1	Engine brand / model / norm		Kubota / WG 3800 / Stage V	
7.2	I.C. Engine power rating		61 kW	
7.3	Rated speed		2300 rpm	
7.4	Number of cylinders / Capacity of cylinders		4 - 3761 cm³	
Miscellaneous				
8.2	Working hydraulic pressure for attachments		190 bar	
8.3	Oil flow rate for attachments		55 l/min	
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 83 dB	

MI 55 G ST5 - Maßzeichnung





 **MANITOU**
HANDLING YOUR WORLD

Hauptsitz

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



Diese Publikation enthält eine Beschreibung der Konfigurationsvarianten und Optionen für Manitou-Produkte, die je nach Ausstattung unterschiedlich sein können. Die in dieser Broschüre vorgestellten Ausstattungen können Teil einer Serie, als Option erhältlich oder je nach Ausführung nicht verfügbar sein. Manitou behält sich das Recht vor, die beschriebenen und dargestellten Spezifikationen jederzeit und ohne Vorankündigung zu ändern. Die angegebenen Spezifikationen sind für den Hersteller nicht bindend. Für weitere Einzelheiten wenden Sie sich bitte an Ihren Manitou-Händler. Es handelt sich nicht um ein vertraglich bindendes Dokument. Die Darstellung der Produkte ist vertraglich nicht bindend. Die Liste der Spezifikationen ist nicht vollständig. Die Logos sowie die visuelle Identität des Unternehmens sind Eigentum von Manitou und dürfen nicht ohne Genehmigung verwendet werden. Alle Rechte vorbehalten. Die in dieser Broschüre enthaltenen Fotos und Diagramme werden nur zu Anschauungs- und Informationszwecken zur Verfügung gestellt.

MANITOU BF SA - Gesellschaft mit beschränkter Haftung mit Verwaltungsrat - Aktienkapital: 39 668 399 Euro - 857 802 508 RCS Nantes