

Technical sheet :

SE 1212

OXYGEN



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric
Working height	h21	11.80 m
Working height maximum (indoor)	h21	11.80 m
Working height maximum (outdoor)	h21'	11.80 m
Platform height maximum (indoor)	h7	9.80 m
Platform height maximum (outdoor)	h7'	9.80 m
Platform capacity	Q	350 kg
Max. capacity on the extension deck		115 kg
Number of people (indoor / outdoor)		3 / 1
Weight and dimensions		
Platform weight*		2880 kg
Platform dimensions (length x width)	lp / ep	2.20 m x 1.15 m
Platform dimensions with extension (length x width)		3.10 m x 1.15 m
Floor height (access)	h20	1.38 m
Overall length	l1	2.43 m
Overall width	b1	1.17 m
Overall height	h17	2.53 m
Overall height (stowed)	h18 ***	1.95 m
Deck opening length	dp	0.90 m
Overall length with platform extension	l15	3.32 m
Outside turning radius - platform	Wa2	2.33 m
Internal turning radius		0 m
Ground clearance with pothole guards deployed	m6	0.02 m
Ground clearance with pothole guards folded	m2	0.08 m
Wheelbase	y	1.75 m
Performances		
Drive speed - stowed		4.50 km/h
Drive speed - raised		0.80 km/h
Gradeability		25 %
Indoor and outdoor max Tilt Rating (Fore and Aft / Side-to-Side)		3.50 ° / 1.50 °
Wheels		
Tires type		Non marking cushion
Standard tires		15 x 5 in / 381 x 125 mm
Drive wheels (front / rear)		2 / 0
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2 / 0
Service brake		Electric
Engine/Battery		
Battery technology		Lead acid
Drive motor power rating		2 x 0.77 kW
Battery voltage		48 V
Number of batteries / Battery capacity		4 / 120 Ah
Battery energy		5.76 kWh
On-board charger (V / A)		24 V / 30 A
Miscellaneous		
Ground Pressure		15.10 daN/cm ²
Hydraulic Pressure		250 bar
Hydraulic tank capacity		24 l
Sound pressure level (platform work station) (LpA)		66.60 dB
Vibration on hands/arms		< 0.30 m/s ²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019

*Varies according to options and standards of the country to which the machine is delivered
 *** With folded guardrail

SE 1212 - Load chart



SE 1212 - Dimensional drawing



Equipment

Standard

2 swing out component trays (hydraulic/electric)

Additional foot-operated horn

Audible alarm and illuminated indicator lamp (leveling, overload, lowering)

Audio warning on descent

Battery - 48V - 120Ah - semi-traction

Battery charge indicator lamp

CAN bus technology

Colour screen with integrated diagnostics

Easy Link with 2 year Service

Electrical front wheel brake

Emergency stop button in platform and on frame

Fold away guard rails with full height swing gate

Hour meter

Manual emergency lowering

Multi-voltage on-board charger - 24V - 30A - IES - Gel - Single-phase

Pothole protection with automatic operation

Side and rear forklift pockets

Sliding basket extension - 90 cm

Optional

Audio warning on all motion

Audio warning on translation

Biodegradable hydraulic oil - Grade 32

Compressed air pipe pre-fitting

Easy Link - With access control keypad

Easy Link - With remote lock

Electric plug - 230V - In the basket - With differential circuit breaker - Europe (E/F) type

LED work light - On basket



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes