Technical sheet:

# MLT-X 850-145 V+






	<b>MLT-X 850-145 V+</b> Created on Dece	mber 14, 2025 at 4:20 PM 01
Capacities		Metric
Max. capacity	Q	4999 kg
Max. lifting height	h3	7.60 m
Maximum outreach		4.55 m
Reach at max. height		4.55 m
Breakout force with bucket		8670 daN
Weight and dimensions		
Unladen weight (with forks)		10780 kg
Ground clearance	m4	0.45 m
Wheelbase	у	2.94 mm
Overall length to carriage (with hitch)	) I11	5.57 m
Overall length to carriage (without hitch)	13	5.54 m
Front overhang	· ·	1.55 mm
Overall width	b1	2.49 m
Overall cab width	b4	0.99 m
Overall height	h17	2.58 m
		132 °
Tilt-down angle	a5	132 12 °
Tilt-up angle	a4	
External turning radius (over tyres)	Wa1	4.04 m
Standard tires	Allian	ce - A580 - 500/70 R24 164A8
Drive wheels (front / rear)		2 / 2
Steering mode	Manicrab, 2	vheel steer, 4 wheel steer, Crab mode
Performances		
Lifting		6.60 s
Lowering		4.90 s
Extension		6.30 s
Retraction		6.30 s
Crowd		4.20 s
Dump		3.10 s
Engine		
Engine brand		Yanmar
Engine norm		Stage IIIA
Engine model		4TN107HT-5SMUF
Number of cylinders - Capacity of cylinders		4 - 4567 cm <sup>3</sup>
Engine power (Hp / kW)		141 Hp / 105 kW
Max. torque / Engine rotation		602 Nm @1500 rpm
Drawbar pull (Laden)		9160 daN
Reversible fan		Standard
Engine cooling system	3 radiators v	vater + intercooler + transmission oil
Transmission		
Transmission type	Conti	nuously variable transmission
Gearbox		M-Vario Plus
Max. travel speed (may vary according to applicable regulations)		40 km/h
Differential lock	Limited slij	differential on front and rear axles
Parking brake	Auto	matic negative parking brake
		d multi-discs braking on front & rear
Service brake		axles
Hydraulics		
Hydraulic pump type	Va	riable displacement pump
Hydraulic flow - Pressure		200 I/min - 270 bar
Flow sharing distributor		Standard
Tank capacities		
Hydraulic tank capacity		141 l
Fuel		142 l
Noise and vibration		
Noise to environment (LwA)		105 dB
Vibration on hands/arms		2.50 m/s <sup>2</sup>
Miscellaneous		
Tractor homologation		Tractor homologation
Cab certification		Cabin ROPS - FOPS level 2
Controls	· ·	JSM
Outilois		JOIVI


## Optional tires tab

	Overall height	Overall width
ALLIANCE - A585 - 500/70 R24 164A8	•	-
MICHELIN - BIBLOAD - 500/70 R24 164A8		
MICHELIN - XHA - 17.5 R25	-	-
MICHELIN - XMCL - 500/70 R24 164A8		
NOKIAN - TRI STEEL - 500/70 R24 164A8	-	-
SOLIDEAL - SOLIDAIR TLH - 14.00 R24		
TRELLEBORG - TH400 - 500/70 R24 164A8	-	-
VREDESTEIN - TRAXION - 500/70 R24 164A8		
VREDESTEIN - ENDURION - 500/70 R24 164A8		

### MLT-X 850-145 V+ - Dimensional drawing








#### MLT-X 850-145 V+ - Load chart

#### Machine on tires with forks Metric







#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes