

Technical sheet :

160 ATJ E

OXYGEN



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|----------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------|
| Working height | h21 | 16.03 m |
| Platform height | h7 | 14.05 m |
| Maximum outreach | | 8.11 m |
| Overhang | | 7.43 m |
| Pendular arm rotation (left / right) | | 90 ° / 90 ° |
| Pendular arm rotation (top / bottom) | | +65 ° / -59.50 ° |
| Platform capacity | Q | 250 kg |
| Turret rotation | | 350 ° |
| Platform rotation (right / left) | | 90 ° / 90 ° |
| Number of people (indoor / outdoor) | | 2 / 2 |
| Weight and dimensions | | |
| Platform weight* | | 6784 kg |
| Platform dimensions (length x width) | lp / ep | 1.80 m x 0.76 m |
| Floor height (access) | h20 | 0.46 m |
| Overall length | l1 | 6.50 m |
| Overall width | b1 | 2.32 m |
| Overall height | h17 | 2.39 m |
| Overall length (stowed) | l9 | 4.48 m |
| Overall height (stowed) | h18 *** | 2.77 m |
| Counterweight offset (turret at 90Å°) | a7 | 0.85 m |
| Counterweight Oversize / Reach | | 0.26 m |
| External turning radius | Wa3 | 3.75 m |
| Ground clearance at centre of wheelbase | m2 | 0.35 m |
| Wheelbase | y | 2.30 m |
| Performances | | |
| Drive speed - stowed | | 5.20 km/h |
| Drive speed - raised | | 0.70 km/h |
| Gradeability | | 45 % |
| Permissible leveling | | 5 ° |
| Wheels | | |
| Tires type | | Foam Filled Non Marking |
| Standard tires | | 840 x 295 mm / 33x12 D610 |
| Drive wheels (front / rear) | | 2 / 2 |
| Steering wheels (front / rear) | | 2 / 2 |
| Braking wheels (front / rear) | | 0 / 2 |
| Engine/Battery | | |
| Battery voltage | | 48 V |
| Battery nominal voltage / capacity | | 48 V / 480 Ah |
| Battery energy | | 23 kWh |
| On-board charger (V / A) | | 48 V / 60 A |
| Miscellaneous | | |
| Number of cycles with STD Battery (HIRD) | | 58 |
| Ground Pressure | | 13 dan/cm2 |
| Hydraulic Pressure | | 250 bar |
| Hydraulic tank capacity | | 24 l |
| Sound pressure level (platform work station) (LpA) | | 70 dB |
| Vibration on hands/arms | | < 2.50 m/s² |
| Standards compliance | | |
| This machine is in compliance with: | | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage) |

*Varies according to options and standards of the country to which the machine is delivered




** According to "REDUCE cycle"

160 ATJ e - Load chart

Load Chart for MEWP Metric



160 ATJ e - Dimensional drawing



Equipment

| Standard |
|-----------------------------------------------------------------------------|
| 220V predisposition in the platform |
| 4 simultaneous movements |
| 4 wheel drive |
| 4 wheel steer with crab mode |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering) |
| Backup electrical pump |
| CAN bus technology |
| Dead man pedal |
| Differential locking on rear axle |
| Easy Link with 2 year Service |
| Easy Manager |
| Emergency stop button in platform and on frame |
| Front axle with limited slip |
| Fully galvanized basket with demountable floor |
| Galvanized basket 1,800 mm |
| Hom in the platform |
| Hour meter |
| LED rotating beacon |
| Large color screen on turret |
| Leveling unlocking |
| Load sensing pump |
| Oscillating front axle |
| Reserve mode |
| Screen information in the basket |
| Simplified lifting system without spreader bar |
| Slinging and securing rings |
| Steer and rotate |

| Optional |
|----------------------------------------------------------|
| 110 V electric plug 16A |
| Audio waming on all motion |
| Audio waming on all motion - White noise |
| Audio waming on movement |
| Audio waming on translation - White noise |
| Biodegradable hydraulic oil - Grade 32 |
| Bottom screen protection |
| Continuous turret rotation |
| Digicode anti-theft device |
| Earthing and shortcircuiting pre-fitting (Bolted ball) |
| Easy Link - With access control keypad |
| Easy link with remote lock |
| Electric centralized filling |
| External pneumatic supply source |
| Foam-filled tires 914 x 381 mm / 36X15D610 |
| Fully galvanized basket 1800mm / 5'11" with lateral door |
| Galvanized basket 2,100 mm |
| Galvanized basket 2.100 mm / 6'11" with lateral door |
| Hydraulic oil heater |
| Iron wheel package |
| Key lock on turret cover |
| Lighting pack |
| Locking the telescope by parameter setting |
| Non-marking Foam Inflated Tires 914 x 381 mm / 36x15D610 |
| OSS - Operation Safety System |
| Personalized paintwork |
| Rail protection |
| Safety kit - Harness + helmet |
| Socket 230 V + differential circuit breaker |
| Two safety kits (helmet + hamess) |
| Water predisposition |
| Working light (x1) on basket |

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes