

Technical sheet :

ATJ 46+ E CR

OXYGEN



 **MANITOU**
HANDLING YOUR WORLD


Capacities		Imperial
Working height	h21	53 ft 3 in
Floor height (access)	h20	1 ft 5 in
Platform height	h7	46 ft 9 in
Max. outreach		27 ft 4 in
Overhang		24 ft 5 in
Pendular arm rotation (left / right)		90 ° / 90 °
Pendular arm rotation (top / bottom)		+66.50 ° / -65.80 °
Platform capacity	Q	899 lb
Turret rotation		360 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		3 / 3
Weight and dimensions		
Platform weight*		17174 lb
Platform dimensions (length x width)	lp / ep	7 ft 7 in x 2 ft 11 in
Overall length	l1	22 ft 7 in
Overall width	b1	7 ft 10 in
Overall height	h17	8 ft 2 in
Overall length (stowed)	l9	15 ft 5 in
Overall height (stowed)	h18	9 ft 8 in
Counterweight offset (turret at 90°)	a7	1 ft 3 in
Counterweight Oversize / Reach		1 ft 2 in
External turning radius	Wa3	12 ft 5 in
Ground clearance at centre of wheelbase	m2	1 ft 3 in
Wheelbase	y	7 ft 7 in
Performances		
Drive speed - stowed		3 mph
Drive speed - raised		0.62 mph
Gradeability		45 %
Permissible leveling		5 °
Wheels		
Tires type		Foam-filled
Standard tires		914 x 370 mm
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 2
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Battery voltage		48 V
Battery nominal voltage / capacity		48 V / 480 Ah
Battery energy		23 kWh
On-board charger (V / A)		48 V / 60 A
Miscellaneous		
Ground Pressure		154 PSI
Hydraulic Pressure		3481 PSI
Hydraulic tank capacity		6 US gal
Noise to environment (LWA)		< 70 dB
Vibration on hands/arms		< 2.50 m/s ²
Standards compliance		
This machine is in compliance with:		ANSI A92.20-2018 CSA B354.6 ICES-002-Issue 6 Standard Canadian EMC

*Varies according to options and standards of the country to which the machine is delivered


** According to "REDUCE cycle"

ATJ 46+ e CR - Load chart

Load Chart for MEWP (Imperial)



ATJ 46+ e CR - Dimensional drawing



Equipment

Standard

110 V American plug with differential circuit breaker
4 simultaneous movements
4 wheel drive
4 wheel steer with crab mode
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Backup electrical pump
CAN bus technology
Continuous turret rotation
Dead man pedal
Differential locking on rear axle
Easy Link with 2 year Service
Easy Manager
Emergency stop button in platform and on frame
Front axle with limited slip
Hom in the platform
Hour meter
LED rotating beacon
Leveling unlocking
Load sensing pump
Oscillating front axle
Painted basket 2.30 m / 7ft 7In for heavy load with lateral door
Reserve mode
Screen information in the basket
Secondary Protection System (SPS)
Simplified lifting system without spreader bar
Slinging and securing rings
Steer and rotate
Turret orientation information

Optional

110v Canadian plug in basket with 3 differential circuit breaker
18" tyres
Additional tool boxes (X2)
Biodegradable hydraulic oil - Grade 32
Biodegradable oil
Bottom screen protection
Digicode anti-theft device
Easy Link - With access control keypad
Easy link - With remote lock
Electric centralized filling
External pneumatic supply source
Iron wheel package
Key lock on turret cover
Lighting pack
Locking the telescope by parameter setting
Non-marking Foam Inflated Tires 914 x 381 mm / 36x15D610
OSS - Operation Safety System
Panel support kit
Personalized paintwork
Tube support kit
Water predisposition
Working light (x1) on basket

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes