

Technical sheet :

# 80 VJR

OXYGEN  
by MANITOU



 **MANITOU**  
HANDLING YOUR WORLD

| Capacities  |         | Metric  |
|---|---------|---|
| Working height  | h21     | 7.65 m  |
| Platform height                                       | h7      | 5.65 m  |
| Maximum outreach                                      |         | 3.20 m  |
| Overhang  |         | 4.12 m  |
| Pendular arm rotation (top / bottom)                  |         | +62 ° / 51 °  |
| Platform capacity                                     | Q       | 200 kg  |
| Turret rotation                                       |         | 350 °   |
| Number of people (indoor / outdoor)                   |         | 2 / 1   |
| Weight and dimensions                                 |         |   |
| Platform weight*                                      |         | 2410 kg   |
| Platform dimensions (length x width)                  | lp / ep | 1.19 m x 0.93 m   |
| Floor height (access)                                 | h20     | 0.41 m  |
| Overall length  | l1      | 2.90 m  |
| Overall width   | b1      | 0.99 m  |
| Overall height  | h17     | 1.99 m  |
| Jib length  | l13     | 1.61 m  |
| Counterweight offset (turret at 90°)                  | a7      | 0.09 m  |
| External turning radius                               | Wa3     | 2.10 m  |
| Ground clearance under pothole protection             | m6      | 0.03 m  |
| Ground clearance at centre of wheelbase               | m2      | 0.09 m  |
| Wheelbase   | y       | 1.20 m  |
| Performances  |         |   |
| Drive speed - stowed                                  |         | 4.50 km/h   |
| Drive speed - raised                                  |         | 0.65 km/h   |
| Gradeability  |         | 25 %  |
| Permissible leveling                                  |         | 2 °   |
| Wheels  |         |   |
| Tires type  |         | Non marking cushion   |
| Standard tires  |         | 16.5-11 1/4 / 406 x 127 mm  |
| Drive wheels (front / rear)                           |         | 0 / 2   |
| Steering wheels (front / rear)                        |         | 2 / 0   |
| Braking wheels (front / rear)                         |         | 0 / 2   |
| Engine/Battery  |         |   |
| Drive motor power rating                              |         | 2 x 0.77 kW   |
| Lift motor power                                      |         | 3 kW  |
| Number of hydraulic pump / Capacity of hydraulic pump |         | 2 x 3.75 cm³  |
| Battery voltage                                       |         | 24 V  |
| Battery capacity                                      |         | 250 Ah  |
| On-board charger (V / A)                              |         | 24 V / 30 A   |
| Miscellaneous   |         |   |
| Number of cycles with STD Battery (HIRD)              |         | 32  |
| Ground Pressure                                       |         | 10.50 daN/cm2   |
| Hydraulic Pressure                                    |         | 140 bar   |
| Hydraulic tank capacity                               |         | 22 l  |
| Noise to environment (LwA)                            |         | < 70 dB   |
| Vibration on hands/arms                               |         | < 0.50 m/s²   |
| Standards compliance                                  |         |   |
| This machine is in compliance with:                   |         | European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019 |

\*Varies according to options and standards of the country to which the machine is delivered

## 80 VJR - Load chart

Load Chart for MEWP Metric



## 80 VJR - Dimensional drawing



# Equipment

## Standard

- Additional foot-operated hom
- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- CAN bus technology
- Easy Link with 2 year Service
- Emergency stop button in platform and on frame
- Fixed pothole protection
- Fork pockets
- Manual emergency lowering
- Multi-function smartview display
- Multi-voltage onboard charger - 48V - 35A - ZIVAN - Gel - Single-phase
- Negative-type braking on rear wheels
- Non-marking rubber tyres
- Pendular arm
- Proportional controls
- Secondary Protection System (SPS)
- Slinging and securing rings
- Toolbox
- Traction battery
- Travel possible at maximum height
- lace floor basket

## Optional

- Audio warning on all motion
- Audio warning on all motion
- Audio warning on descent
- Basket controls protection
- Basket with hinged doors
- Biodegradable hydraulic oil - Grade 32
- Central filling system
- Charger plug - 110V - 16A - United Kingdom (G) type
- Cold weather protection oil
- Easy Link - With access control keypad
- Easy Link - With remote lock
- Electrical pre-fitting - 230V - With IP65 reel
- Harness detection with a warning light
- LED amber strobe light on the basket
- LED strobe light on the turret
- LED work light - On basket
- Maintenance-free battery
- Personalized paintwork
- Safety kit - Helmet and harness
- Turret orientation detection

**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes