

Ficha técnica :

# 150 AETJ-C

OXYGEN  
by MANITOU



 **MANITOU**  
HANDLING YOUR WORLD

| Capacities                               |         | Métrico  |
|--|---------|--|
| Working height                           | h21     | 14.60 m  |
| Platform height                          | h7      | 12.60 m  |
| Max. outreach                            |         | 7.13 m   |
| Overhang                                 |         | 7.07 m   |
| Pendular arm rotation (top / bottom)     |         | +65 ° / -65 °  |
| Platform capacity                        | Q       | 220 kg   |
| Turret rotation                          |         | 355 °  |
| Platform rotation (right / left)         |         | 66 ° / 59 °  |
| Number of people (indoor / outdoor)      |         | 2 / 2  |
| Weight and dimensions                    |         |  |
| Platform weight*                         |         | 6975 kg  |
| Platform dimensions (length x width)     | lp / ep | 1.20 m x 0.92 m  |
| Floor height (access)                    | h20     | 0.40 m   |
| Overall length                           | l1      | 6.05 m   |
| Overall width                            | b1      | 1.50 m   |
| Overall height                           | h17     | 1.97 m   |
| Overall length (stowed)                  | l9      | 4.40 m   |
| Overall height (stowed)                  | h18 *** | 2.08 m   |
| Jib length                               | l13     | 1.26 m   |
| Counterweight offset (turret at 90°)     | a7      | 0.12 m   |
| External turning radius                  | Wa3     | 3.96 m   |
| Ground clearance at centre of wheelbase  | m2      | 0.14 m   |
| Wheelbase                                | y       | 2 m  |
| Performances                             |         |  |
| Drive speed - stowed                     |         | 5 km/h   |
| Drive speed - raised                     |         | 0.60 km/h  |
| Gradeability                             |         | 22 %   |
| Permissible leveling                     |         | 3 °  |
| Wheels                                   |         |  |
| Tires type                               |         | Solid non-marking tires  |
| Standard tires                           |         | 24 x 7.5 in / 600 x 190 mm   |
| Drive wheels (front / rear)              |         | 0 / 2  |
| Steering wheels (front / rear)           |         | 2 / 0  |
| Braking wheels (front / rear)            |         | 0 / 2  |
| Engine/Battery                           |         |  |
| Electric engine power rating             |         | 2 x 3 kW   |
| Lift motor power                         |         | 3.70 kW  |
| Battery nominal voltage / capacity       |         | 48 V / 240 Ah  |
| Battery energy                           |         | 11 kWh   |
| On-board charger (V / A)                 |         | 48 V / 30 A  |
| Miscellaneous                            |         |  |
| Number of cycles with STD Battery (HIRD) |         | 46   |
| Ground Pressure                          |         | 13.50 dan/cm <sup>2</sup>  |
| Hydraulic Pressure                       |         | 210 bar  |
| Hydraulic tank capacity                  |         | 15 l   |
| Noise to environment (LWA)               |         | < 70 dB  |
| Vibration on hands/arms                  |         | < 0.52 m/s <sup>2</sup>  |
| Standards compliance                     |         |  |
| This machine is in compliance with:      |         | European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage) |

\*Varies according to options and standards of the country to which the machine is delivered

## 150 AETJ-C - Diagramas de carga

Load Chart metric



## 150 AETJ-C - Diagrama dimensional



# Equipamiento

## Estándar

230V Predisposition  
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  
CAN bus technology  
Easy Link with 2 year Service  
Emergency stop button in platform and on frame  
Hom in the platform  
Manual emergency lowering  
Multi-function smartview display  
Multi-voltage integrated charger  
Negative-type braking on rear wheels  
Non-marking rubber tyres  
Pendular arm  
Platform with open-work floor  
Proportional controls  
Secondary Protection System (SPS)  
Slinging and securing rings  
Tool box in platform  
Traction battery  
Travel possible at maximum height

## Opcional

110 or 230V plug with differential circuit breaker  
Audio warning on all motion  
Audio warning on movement  
Biodegradable hydraulic oil - Grade 32  
Centralized filling of the battery  
Cold weather protection oil  
Easy Link - With access control keypad  
Easy link with remote lock  
External pneumatic supply source  
High capacity starting battery  
Maintenance-free battery  
Non-marking Foam Inflated Tires 914 x 381 mm / 36x15D610  
Personalized paintwork  
Protective cover for control panel  
Rail protection  
Safety kit - Harness + helmet  
Turret orientation information  
Water predisposition  
Working light (x1) on basket



**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes