


Technical sheet :

200 ATJ E 4WS

OXYGEN




 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric
Working height	h21	20 m
Platform height	h7	18 m
Maximum outreach		11.57 m
Overhang		7.91 m
Pendular arm rotation (top / bottom)		+65 ° / -60 °
Platform capacity	Q	250 kg
Turret rotation		350 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		7530 kg
Platform dimensions (length x width)	l _p / ep	2.10 m x 0.76 m
Floor height (access)	h20	0.35 m
Overall length	l1	8.34 m
Overall width	b1	2.38 m
Overall height	h17	2.46 m
Overall length (stowed)	l9	6.06 m
Overall height (stowed)	h18 ***	2.74 m
Counterweight offset (turret at 90°)	a7	0.61 m
External turning radius	Wa3	3.78 m
Ground clearance at centre of wheelbase	m2	0.38 m
Wheelbase	y	2.30 m
Performances		
Drive speed - stowed		5.30 km/h
Drive speed - raised		0.65 km/h
Gradeability		40 %
Permissible leveling		4 °
Wheels		
Tires type		Foam Filled Non Marking
Standard tires		914 x 381 mm / 36X15D610
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 2
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Battery voltage		48 V
Battery nominal voltage / capacity		48 V / 460 Ah
Battery energy		22 kWh
On-board charger (V / A)		48 V / 60 A
Miscellaneous		
Number of cycles with STD Battery (HIRD)		41
Hydraulic Pressure		240 bar
Hydraulic tank capacity		24 l
Noise to environment (L _{WA})		70 dB
Vibration on hands/arms		0.62 m/s ²
Standards compliance		
This machine is in compliance with:	European directives: 2006/42/EC - Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019	




*Varies according to options and standards of the country to which the machine is delivered

200 ATJ e 4WS - Load chart

Load Chart metric



200 ATJ e 4WS - Dimensional drawing




Equipment

Standard

- 230V Predisposition
- 4 simultaneous movements
- 4 wheel drive
- 4 wheel steer with crab mode
- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- Backup electrical pump
- CAN bus technology
- Dead man pedal
- Differential locking on rear axle
- Easy Link with 2 year Service
- Emergency stop button in platform and on frame
- Flat Led Rotating Beacon
- Front axle with limited slip
- Galvanized basket 2,100 mm
- Horn in the platform
- Hour meter
- Integrated diagnostic assistance
- Large color screen on turret
- Lead acid batteries
- Load sensing pump
- Multi-voltage integrated charger Zivan 48V /60 A
- Oscillating front axle
- Protective cover for control panel
- Reserve mode
- Screen information in the basket
- Secondary Protection System (SPS)
- Slinging and securing rings
- Tool box in platform
- Travel possible at maximum height
- Turret orientation information

Optional

- 110 or 230V plug with differential circuit breaker
- Audio warning on all motion
- Audio warning on translation
- Audio warning on translation - White noise
- Biodegradable hydraulic oil - Grade 32
- Coded anti-start
- Digicode anti-theft device
- Earthing and shortcircuiting pre-fitting (Bolted ball)
- Easy Link - With access control keypad
- Easy link with remote lock
- Electric centralized filling
- External pneumatic supply source
- Fully galvanized basket 1800mm / 5'11" with lateral door
- Galvanized basket 1,800 mm
- Galvanized basket with side swing gate - Width: 2100 mm (6 ft. 11 in.)
- Hydraulic oil heater
- Iron wheel package
- Key lock on turret covers
- LED amber strobe light on the basket
- LED work light - On basket
- Lighting pack
- Locking the telescope by parameter setting
- OSS - Obstacle Detection
- OSS - Operation Safety System
- Personalized paintwork
- Safety kit - Harness + helmet
- Water predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière
 44150 Ancenis Cedex - France
 Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes