

Technical sheet :

220 TJ ST5




 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric
Working height	h21	21.77 m
Platform height	h7	19.77 m
Maximum outreach		17.63 m
Pendular arm rotation (top / bottom)		+69 ° / -66 °
Platform capacity	Q	230 kg
Turret rotation		360 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		12000 kg
Platform dimensions (length x width)	l p / ep	2.10 m x 0.76 m
Floor height (access)	h20	0.39 m
Overall length	l1	9.81 m
Overall width	b1	2.48 m
Overall height	h17	2.66 m
Overall length (stowed)	l9	7.29 m
Overall height (stowed)	h18 ***	2.72 m
Jib length	l13	2 m
Counterweight offset (turret at 90°)	a7	1.35 m
External turning radius	Wa3	6.19 m
Ground clearance at centre of wheelbase	m2	0.44 m
Wheelbase	y	2.80 m
Performances		
Drive speed - stowed		4.40 km/h
Drive speed - raised		1 km/h
Gradeability		40 %
Permissible leveling		4 °
Wheels		
Tires type		Solid tires
Standard tires		40 x 14 in / 1025 x 365 mm
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Engine brand / model		Yanmar - 3TNV88C
Engine norm		Stage V
Engine power (Hp / kW)		37 Hp / 27.50 kW
Miscellaneous		
Ground Pressure		18.20 dan/cm ²
Hydraulic Pressure		340 bar
Hydraulic tank capacity		94 l
Fuel		76 l
Sound pressure level (platform work station) (LpA)		82 dB
Daily consumption **		5.48 l
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC - Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019


*Varies according to options and standards of the country to which the machine is delivered

220 TJ ST5 - Load chart

Load Chart for MEWP Metric



220 TJ ST5 - Dimensional drawing



Equipment

Standard

- 230V Predisposition
- 4 simultaneous movements
- 4 wheel drive
- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- Backup electrical pump
- Connected machine
- Continuous turret rotation
- Dead man pedal
- Differential locking on rear axle
- Easy fast slinging system
- Electronic platform compensation
- Emergency stop button in platform and on frame
- Engine compartment with key lock
- Engine mounted on sliding platform
- Engine with DPF (Diesel Particulate Filter)
- Front axle with limited slip
- Fuel gauge with low level indicator
- Fully galvanized basket with removable floor - Width: 2100 mm (6 ft. 11 in.)
- Hour meter
- Hydraulic oil heater
- Integrated diagnostic assistance
- LED rotating beacon
- LS pump
- Large color screen on turret
- Leveling unlocking
- Oscillating front axle
- Proportional controls
- Secondary Protection System (SPS)
- Stop & Go system
- Turret orientation information
- Yellow and black safety stickers on moving parts

Optional

- 110 or 230V plug with differential circuit breaker
- Audio warning on all motion
- Audio warning on translation
- Battery blanket
- Battery cut-off
- Biodegradable hydraulic oil - Grade 32
- Earthing and shortcircuiting pre-fitting (Bolted ball)
- Easy Link - With access control keypad
- Easy link with remote lock
- Engine Block Heater
- External pneumatic supply source
- Galvanized basket with side swing gate - Width: 2100 mm (6 ft. 11 in.)
- Hydraulic oil for cold temperature
- Hydraulic oil heater
- Key lock on fuel tank
- LED amber strobe light on the basket
- LED work light - On basket
- Non marking tires
- On-board generator (3,5 or 5 kW)
- Packing for containerization
- Personalized paintwork
- Rail protection
- Reflective stripes
- Remote control for transport
- Safety kit - Harness + helmet
- Safety valve
- Screen protection on the lower box control
- Starter battery charger and engine pre-heater with common outlet
- Water predisposition
- Working light



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes