

Technical sheet :

180 ATJ CR




 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|---|---------|---|
| Working height | h21 | 18.18 m |
| Platform height | h7 | 16.18 m |
| Maximum outreach | | 10.51 m |
| Overhang | | 7.42 m |
| Pendular arm rotation (top / bottom) | | +65 ° / -59.50 ° |
| Platform capacity | Q | 230 kg |
| Turret rotation | | 360 ° |
| Platform rotation (right / left) | | 90 ° / 90 ° |
| Number of people (indoor / outdoor) | | 2 / 2 |
| Weight and dimensions | | |
| Platform weight* | | 7430 kg |
| Platform dimensions (length x width) | lp / ep | 1.80 m x 0.80 m |
| Floor height (access) | h20 | 0.43 m |
| Overall length | l1 | 7.79 m |
| Overall width | b1 | 2.32 m |
| Overall height | h17 | 2.47 m |
| Overall length (stowed) | l9 | 5.56 m |
| Overall height (stowed) | h18 *** | 2.56 m |
| Counterweight offset (turret at 90Å°) | a7 | 0.22 m |
| External turning radius | Wa3 | 3.63 m |
| Ground clearance at centre of wheelbase | m2 | 0.40 m |
| Wheelbase | y | 2.20 m |
| Performances | | |
| Drive speed - stowed | | 5 km/h |
| Drive speed - raised | | 1 km/h |
| Gradeability | | 45 % |
| Permissible leveling | | 5 ° |
| Wheels | | |
| Tires type | | Foam-filled |
| Drive wheels (front / rear) | | 2 / 2 |
| Steering wheels (front / rear) | | 2 / 2 |
| Braking wheels (front / rear) | | 0 / 2 |
| Engine/Battery | | |
| Engine brand / model | | Kubota - D1105-E4B |
| Engine norm | | Stage V |
| I.C. Engine power rating / Power | | 24.80 Hp / 18.50 kW |
| Miscellaneous | | |
| Ground Pressure | | 10 dan/cm2 |
| Hydraulic Pressure | | 340 bar |
| Hydraulic tank capacity | | 54 l |
| Fuel tank | | 52 l |
| Daily consumption ** | | 4.27 l |
| Standards compliance | | |
| This machine is in compliance with: | | European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019 |

*Varies according to options and standards of the country to which the machine is delivered

180 ATJ CR - Dimensional drawing



Equipment

| Standard |
|--|
| 220V predisposition in the platform |
| 3D |
| 4 simultaneous movements |
| 4 wheel drive |
| 4 wheel steer with crab mode |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering) |
| Backup electrical pump |
| Basket 1,800 mm |
| CAN bus technology |
| Continuous turret rotation |
| Differential locking on rear axle |
| Easy Link with 2 year Service |
| Emergency stop button in platform and on frame |
| Engine compartment with key lock |
| Fuel gauge with low level indicator |
| Fully galvanized basket with removable floor - Width: 2100 mm (6 ft. 11 in.) |
| Hour meter |
| Integrated diagnostic assistance |
| Leveling unlocking |
| Load sensing pump |
| Operator presence pedal |
| Oscillating front axle |
| Secondary Protection System (SPS) |
| Steer and rotate |
| Stop & Go system |
| Optional |
| Battery charger |
| Battery cut-off |
| Coded anti-start |
| Cold weather protection oil |
| Exhaust line protection, spark arrestor and fume reduction system |
| Fully galvanized basket 1800mm / 5'11" with lateral door |
| Galvanized basket 2,100 mm |
| Galvanized basket with side swing gate - Width: 2100 mm (6 ft. 11 in.) |
| High capacity starting battery |
| Lockable fuel cap |
| Non-marking tyres |
| On-board generator (3,5 or 5 kW) |
| Personalized paintwork |
| Safety kit - Harness + helmet |
| Socket 230 V + differential circuit breaker |
| Spark arresting muffler |
| Water heater |
| Water predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes