

Technical sheet :

# 280 TJ ST5



 **MANITOU**  
HANDLING YOUR WORLD


Capacities		Metric
Working height	h21	27.73 m
Platform height	h7	25.73 m
Maximum outreach		21.45 m
Pendular arm rotation (top / bottom)		+56.80 ° / -62 °
Platform capacity / capacity (maximum)	Q	240 kg / 350 kg
Turret rotation		360 °
Platform rotation (right / left)		90 ° / 90 °
Number of people (indoor / outdoor)		3 / 2
Weight and dimensions		
Platform weight*		16900 kg
Platform dimensions (length x width)	l p / ep	2.30 m x 0.90 m
Floor height (access)	h20	0.48 m
Overall length	l1	11.36 m
Overall width	b1	2.48 m
Overall height	h17	2.73 m
Overall length (stowed)	j9	8.09 m
Overall height (stowed)	h18 ***	2.71 m
Jib length	l13	3.80 m
Counterweight offset (turret at 90°)	a7	1.43 m
External turning radius	Wa3	4.35 m
Ground clearance at centre of wheelbase	m2	0.41 m
Wheelbase	y	2.80 m
Performances		
Drive speed - stowed		4.50 km/h
Drive speed - raised		0.80 km/h
Gradeability		35 %
Permissible leveling		4 °
Wheels		
Tires type		Solid tires
Standard tires		40 x 14 in / 1025 x 365 mm
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 2
Braking wheels (front / rear)		2 / 2
Engine/Battery		
Engine brand / model		Yanmar - 4TNV88C
Engine norm		Stage V
Engine power (Hp / kW)		46 Hp / 34.30 kW
Miscellaneous		
Ground Pressure		21.30 dan/cm²
Hydraulic Pressure		400 bar
Hydraulic tank capacity		94 l
Fuel		76 l
Sound pressure level (platform work station) (LpA)		79 dB
Vibration on hands/arms		0.50 m/s²
Daily consumption **		8 l
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019

\*Varies according to options and standards of the country to which the machine is delivered


\*\* According to "REDUCE cycle"

## 280 TJ ST5 - Load chart

Load Chart for MEWP Metric



## 280 TJ ST5 - Dimensional drawing



# Equipment

## Standard

- 230V Predisposition
- 4 simultaneous movements
- 4 wheel drive
- 4 wheel steer with crab mode
- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- Backup electrical pump
- Connected machine
- Continuous turret rotation
- Dead man pedal
- Differential locking on rear axle
- Electronic platform compensation
- Emergency stop button in platform and on frame
- Engine compartment with key lock
- Engine on swivel chair
- Engine with DPF (Diesel Particulate Filter)
- Front axle with limited slip
- Fuel gauge with low level indicator
- Heavy-duty painted basket 2.30 m
- Horn in the platform
- Hour meter
- Integrated diagnostic assistance
- LED rotating beacon
- LS pump
- Large color screen on turret
- Leveling unlocking
- Oscillating front axle
- Painted basket for heavy loads 2,300 mm (7ft 7 in.)
- Protective cover for control panel
- Remote control for transport
- Secondary Protection System (SPS)
- Stop & Go system
- Telescopic jib
- Turret orientation information
- X Y function
- Yellow and black safety stickers on moving parts

## Optional

- Additional storage boxes
- Audio warning on all motion
- Audio warning on movement
- Battery blanket
- Battery charger automatic start
- Battery cut-off
- Biodegradable hydraulic oil - Grade 32
- Cold weather protection oil
- Earthing and shortcircuiting pre-fitting (Bolted ball)
- Easy Link with access control keypad
- Easy link with remote lock
- Engine Block Heater
- External pneumatic supply source
- Hydraulic oil heater
- Key lock on fuel tank
- LED amber strobe light on the basket
- Non marking tires
- On-board generator (3,5 or 5 kW)
- Packing for containerization
- Painted basket - For heavy loads - Width: 2300 mm (7 ft. 7 in.)
- Painted narrow basket for heavy loads 1800mm (5 ft 11 in.)
- Panel cradle
- Personalized paintwork
- Pipe cradle
- Rail protection
- Reflective stripes
- Safety kit - Harness + helmet
- Socket 230 V + differential circuit breaker
- Water predisposition
- Working light



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
 44150 Ancenis Cedex - France  
 Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes