Technical sheet:

SE 0808








	SE 0808 Cleate	d on December 15, 2025 at 9:03 PM U
Capacities		Metric
Working height	h21	7.80 m
Working height maximum (indoor)	h21	7.80 m
Working height maximum (outdoor)	h21'	7.80 m
Platform height maximum (indoor)	h7	5.80 m
Platform height maximum (outdoor)	h7'	5.80 m
Platform capacity	Q	230 kg
Max. capacity on the extension deck		115 kg
Number of people (indoor / outdoor)		2/1
Veight and dimensions		27.
Platform weight*		1500 kg
Platform dimensions (length x width)	lp / ep	1.64 m x 0.75 m
Platform dimensions with extension (length x width)	ір / ер	2.54 m x 0.75 m
, ,	100	
Floor height (access)	h20	1.02 m
Overall length	l1	1.88 m
Overall width	b1	0.81 m
verall height	h17	2.17 m
Overall height (stowed)	h18 ***	1.99 m
leck opening length	dp	0.90 m
Overall length with platform extension	l15	2.76 m
Outside turning radius - platform	Wa2	1.73 m
nternal turning radius		0 m
Fround clearance with pothole guards deployed	m6	0.01 m
round clearance with pothole guards folded	m2	0.05 m
Vheelbase	y	1.40 m
Performances		
Drive speed - stowed		4.50 km/h
Drive speed - raised		0.80 km/h
aise speed (laden) / Lower speed (laden)		17 s / 18 s
Gradeability		25 %
ndoor and outdoor max Tilt Rating (Fore and Aft / Side-to-Side)		3.50 ° / 1.50 °
Vheels		3.30 7 1.30
Tires type		Non marking cushion
tandard tires		12 x 4 in / 305 x 106 mm
		2 / 0
Irive wheels (front / rear)		
teering wheels (front / rear)		2 / 0
traking wheels (front / rear)		2 / 0
ervice brake		Electric
ingine/Battery		
lattery technology		Semi-traction
rive motor power rating		0.55 kW
lattery voltage		24 V
lumber of batteries / Battery capacity		4 / 185 Ah
lattery energy		4.44 kWh
n-board charger (V / A)		24 V / 30 A
fiscellaneous		
lumber of cycles with STD Battery (HIRD)		146
lydraulic Pressure		250 bar
lydraulic tank capacity		12
ound pressure level (platform work station) (LpA)		66.60 dB
fibration on hands/arms		0.50 m/s²
Standards compliance		5.55 mg 6
his machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EN according to EN 12895 / 2015 +A1 / 2019


^{*}Varies according to options and standards of the country to which the machine is delivered *** With folded guardrail

SE 0808 - Load chart

Load Chart for MEWP Metric



SE 0808 - Dimensional drawing



Equipment

2 swing out component trays (hydraulic/electric) Audible alarm and illuminated indicator lamp (leveling, overload, lowering) Battery - 24V - 185Ah - semi-traction Battery charge indicator lamp CAN bus technology Colour screen with integrated diagnostics Descent alarm Easy Link with 2 year Service Electrical front wheel brake Emergency stop button in platform and on frame Folding rails with full height access gate Horn in the platform Hour meter Manual emergency lowering Multi-voltage on-board charger - 24V - 30A - Single-phase Pothole protection with automatic operation Side and rear forklift pockets Sliding basket extension - 90 cm

Optional Audio warning on all motion Audio warning on translation Easy Link - With access control keypad Easy link with remote lock Electric plug - 110 or 230V - In the basket - With differential circuit breaker - European type External pneumatic supply source Working light (x1) on basket





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes