

Technical sheet :

# SE 1008

OXYGEN



 **MANITOU**  
HANDLING YOUR WORLD

| Capacities   |         | Metric  |
|--|---------|---|
| Working height   | h21     | 9.99 m  |
| Working height maximum (indoor)                                  | h21     | 9.99 m  |
| Working height maximum (outdoor)                                 | h21'    | 9 m   |
| Platform height maximum (indoor)                                 | h7      | 7.99 m  |
| Platform height maximum (outdoor)                                | h7'     | 7 m   |
| Platform capacity  | Q       | 230 kg  |
| Max. capacity on the extension deck                              |         | 115 kg  |
| Number of people (indoor / outdoor)                              |         | 2 / 1   |
| Weight and dimensions  |         |   |
| Platform weight*   |         | 2210 kg   |
| Platform dimensions (length x width)                             | lp / ep | 2.20 m x 0.79 m   |
| Platform dimensions with extension (length x width)              |         | 3.10 m x 0.79 m   |
| Floor height (access)  | h20     | 1.25 m  |
| Overall length   | l1      | 2.42 m  |
| Overall width  | b1      | 0.82 m  |
| Overall height   | h17     | 2.17 m  |
| Overall height (stowed)  | h18 *** | 1.98 m  |
| Deck opening length  | dp      | 0.90 m  |
| Overall length with platform extension                           | l15     | 3.31 m  |
| Outside turning radius - platform                                | Wa2     | 2.17 m  |
| Internal turning radius  |         | 0 m   |
| Ground clearance with pothole guards deployed                    | m6      | 0.02 m  |
| Ground clearance with pothole guards folded                      | m2      | 0.08 m  |
| Wheelbase  | y       | 1.75 m  |
| Performances   |         |   |
| Drive speed - stowed   |         | 4.50 km/h   |
| Drive speed - raised   |         | 0.80 km/h   |
| Raise speed (laden) / Lower speed (laden)                        |         | 33 s / 32 s   |
| Gradeability   |         | 25 %  |
| Indoor and outdoor max Tilt Rating (Fore and Aft / Side-to-Side) |         | 3.50 ° / 1.50 °   |
| Wheels   |         |   |
| Tires type   |         | Non marking   |
| Standard tires   |         | 15 x 5 in / 381 x 125 mm  |
| Drive wheels (front / rear)                                      |         | 2 / 0   |
| Steering wheels (front / rear)                                   |         | 2 / 0   |
| Braking wheels (front / rear)                                    |         | 2 / 0   |
| Service brake  |         | Electric  |
| Engine/Battery   |         |   |
| Battery technology   |         | Semi-traction   |
| Number of batteries / Battery nominal voltage / Battery capacity |         | 4 / 6 V / 185 Ah  |
| Battery energy   |         | 4.40 kW/h   |
| On-board charger (V / A)   |         | 24 V / 30 A   |
| Miscellaneous  |         |   |
| Hydraulic Pressure   |         | 250 bar   |
| Hydraulic tank capacity  |         | 24 l  |
| Sound pressure level (platform work station) (LpA)               |         | 66.60 dB  |
| Vibration on hands/arms  |         | < 0.50 m/s <sup>2</sup>   |
| Standards compliance   |         |   |
| This machine is in compliance with:                              |         | European directives: 2006/42/EC- Machinery (revised EN280-1:2022) - 2004/108/EC (EMC) - EMC according to EN 12895 / 2015 +A1 / 2019 |

\*Varies according to options and standards of the country to which the machine is delivered

\*\*\* With folded guardrail

SE 1008 - Load chart



SE 1008 - Dimensional drawing



# Equipment

## Standard

2 swing out component trays (hydraulic/electric)  
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  
Battery - 24V - 185Ah - semi-traction  
Battery charge indicator lamp  
CAN bus technology  
Colour screen with integrated diagnostics  
Descent alarm  
Easy Link with 2 year Service  
Electrical front wheel brake  
Emergency stop button in platform and on frame  
Folding rails with full height access gate  
Horn in the platform  
Hour meter  
Management of working height according to working place (indoor/outdoor)  
Manual emergency lowering  
Multi-voltage on-board charger - 24V - 30A - Single-phase  
Pothole protection with automatic operation  
Side and rear forklift pockets  
Sliding basket extension - 90 cm

## Optional

Audio warning on all motion  
Audio warning on translation  
Easy Link - With access control keypad  
Easy link with remote lock  
Electric plug - 110 or 230V - In the basket - With differential circuit breaker - European type  
External pneumatic supply source  
Working light (x1) on basket



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes