

Technical sheet :

# SE 1932

OXYGEN



 **MANITOU**  
HANDLING YOUR WORLD


Capacities		Imperial
Working height	h21	25 ft 7 in
Working height maximum (indoor)	h21	25 ft 7 in
Working height maximum (outdoor)	h21'	25 ft 7 in
Platform height maximum (indoor)	h7	19 ft
Platform height maximum (outdoor)	h7'	19 ft
Platform capacity	Q	507 lb
Max. capacity on the extension deck		254 lb
Number of people (indoor / outdoor)		2 / 1
Weight and dimensions		Imperial
Platform weight*		3307 lb
Platform dimensions (length x width)	l <sub>p</sub> / ep	5 ft 5 in x 2 ft 6 in
Platform dimensions with extension (length x width)		8 ft 4 in x 2 ft 6 in
Floor height (access)	h20	3 ft 4 in
Overall length	l1	6 ft 2 in
Overall width	b1	2 ft 8 in
Overall height	h17	7 ft 1 in
Overall height (stowed)	h18 ***	6 ft 6 in
Deck opening length	dp	2 ft 11 in
Overall length with platform extension	l15	9 ft 1 in
Outside turning radius - platform	Wa2	5 ft 8 in
Internal turning radius		0 in
Ground clearance with pothole guards deployed	m6	0 in
Ground clearance with pothole guards folded	m2	2 in
Wheelbase	y	4 ft 7 in
Performances		Imperial
Drive speed - stowed		3 mph
Drive speed - raised		0.50 mph
Raise speed (laden) / Lower speed (laden)		17 s / 18 s
Gradeability		25 %
Indoor and outdoor max Tilt Rating (Fore and Aft / Side-to-Side)		3.50 ° / 1.50 °
Wheels		Imperial
Tires type		Non marking cushion
Standard tires		12 x 4 in / 305 x 106 mm
Drive wheels (front / rear)		2 / 0
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2 / 0
Service brake		Electric
Engine/Battery		Imperial
Battery technology		Semi-traction
Drive motor power rating		0.55 kW
Battery voltage		24 V
Number of batteries / Battery capacity		4 / 185 Ah
Battery energy		4.40 kWh
On-board charger (V / A)		24 V / 30 A
Miscellaneous		Imperial
Number of cycles with STD Battery (HIRD)		146
Hydraulic Pressure		3626 PSI
Hydraulic tank capacity		3 US gal
Sound pressure level (platform work station) (L <sub>pA</sub> )		66.60 dB
Vibration on hands/arms		2 ft/s <sup>2</sup>
Standards compliance		Imperial
This machine is in compliance with:		ANSI A92.20-2018 CSA B354.6 ICES-002-Issue 6 Standard Canadian EMC

\*Varies according to options and standards of the country to which the machine is delivered




\*\*\* With folded guardrail

## SE 1932 - Load chart

## Load Chart for MEWP (Imperial)



## SE 1932 - Dimensional drawing



# Equipment

## Standard

- 110 V American plug with differential circuit breaker
- 2 swing out component trays (hydraulic/electric)
- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- Audio warning on all motion
- Battery - 24V - 185Ah - semi-traction
- Battery charge indicator lamp
- CAN bus technology
- Colour screen with integrated diagnostics
- Easy Link with 2 year Service
- Electrical front wheel brake
- Emergency stop button in platform and on frame
- Folding rails with full height access gate
- Horn in the platform
- Hour meter
- Manual emergency lowering
- Multi-voltage on-board charger - 24V - 30A - Single-phase
- Pothole protection with automatic operation
- Side and rear forklift pockets
- Sliding basket extension - 90 cm

## Optional

- Easy Link - With access control keypad
- Easy link with remote lock
- External pneumatic supply source
- Fixed anti-shearing protection
- Working light (x1) on basket



# **MANITOU** HANDLING YOUR WORLD

## Head Office

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France  
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes