

Technical sheet :

# 3250V



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric	
Operating Capacity At 50% Tipping Load		1474 kg	
Rated Operating Capacity with Optional Counterweight		1565 kg	
Operating Weight		4128 kg	
Tipping capacity		2948 kg	
Weight and dimensions			
Wheelbase	y	1321 mm	
Overall Operating Height - Fully Raised	h27	4389 mm	
Height to Hinge Pin - Fully Raised	h28	3409 mm	
Overall Height to top of ROPS	h17	2084 mm	
Dump angle at full height	a5	41 °	
Dump height	h29	2634 mm	
Overall length with bucket	l16	3922 mm	
Dump reach - Full height	r6	846 mm	
Rollback at ground	a13	29 °	
Rollback Angle at Full Height	a4	94 °	
Seat to ground height	h30	1039 mm	
Overall width less bucket	b1	1852 mm	
Bucket Width	e1	1880 mm	
Ground clearance	m4	209 mm	
Overall length - Less Bucket	l2	3124 mm	
Clearance Radius - Front with Bucket	b18	2299 mm	
Performances			
Travel speed (unladen)		10.70 km/h	
Travel Speed with Two-Speed Option - Maximum		17.30 km/h	
Wheels			
Standard tires		12 x 16.5	
Engine			
Engine brand		Yanmar	
Engine model		4TNV98CT-9NGL	
Max. torque / Engine rotation		294 Nm / 1625 rpm	
Power source		Battery	
Engine power (Hp / kW)		72 Hp / 53.70 kW	
Starter		3 kW	
Hydraulics			
Standard flow - Auxiliary hydraulics		94.60 l/min	
Auxiliary Hydraulic Pressure		237.86 bar	
High-Flow Auxiliary Hydraulics - Option		128.70 l/min	
High-Flow Auxiliary Hydraulics Pressure - Option		229.25 bar	
Tank capacities			
Fuel		106 l	
Hydraulic tank capacity		30.30 l	



# **MANITOU** HANDLING YOUR WORLD

## Head Office

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France  
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes