

Technical sheet :

# 3600V

---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Imperial
Operating Capacity At 50% Tipping Load		3600 lb
Rated Operating Capacity with Optional Counterweight		3801 lb
Operating Weight		10320 lb
Tipping capacity		7200 lb
Weight and dimensions		
Wheelbase	y	52 in
Overall Operating Height - Fully Raised	h27	175 in
Height to Hinge Pin - Fully Raised	h28	136 in
Overall Height to top of ROPS	h17	84 in
Dump angle at full height	a5	41 °
Dump height	h29	105 in
Overall length with bucket	l16	156 in
Dump reach - Full height	r6	31 in
Rollback at ground	a13	29 °
Rollback Angle at Full Height	a4	94 °
Seat to ground height	h30	43 in
Overall width less bucket	b1	75 in
Bucket Width	e1	84 in
Ground clearance	m4	10 in
Overall length - Less Bucket	l2	125 in
Clearance Radius - Front with Bucket	b18	93 in
Performances		
Travel speed (unladen)		7 mph
Travel Speed with Two-Speed Option - Maximum		12 mph
Wheels		
Standard tires		14.00 x 17.5 HD
Engine		
Engine brand		Deutz
Engine model		TCD3.6
Max. torque / Engine rotation		339 ft/lbs / 1600 rpm
Power source		Battery
Engine power (Hp / kW)		114 Hp / 85 kW
Starter		4 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		25 US gpm
Auxiliary Hydraulic Pressure		3450 PSI
High-Flow Auxiliary Hydraulics - Option		40 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		3450 PSI
Tank capacities		
Fuel		28 US gal
Hydraulic tank capacity		8 US gal

**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes