

Technical sheet :

3600V



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|--|-----|-------------------|
| Operating Capacity At 50% Tipping Load | | 1633 kg |
| Rated Operating Capacity with Optional Counterweight | | 1724 kg |
| Operating Weight | | 4681 kg |
| Tipping capacity | | 3266 kg |
| Weight and dimensions | | |
| Wheelbase | y | 1321 mm |
| Overall Operating Height - Fully Raised | h27 | 4435 mm |
| Height to Hinge Pin - Fully Raised | h28 | 3454 mm |
| Overall Height to top of ROPS | h17 | 2134 mm |
| Dump angle at full height | a5 | 41 ° |
| Dump height | h29 | 2678 mm |
| Overall length with bucket | l16 | 3968 mm |
| Dump reach - Full height | r6 | 798 mm |
| Rollback at ground | a13 | 29 ° |
| Rollback Angle at Full Height | a4 | 94 ° |
| Seat to ground height | h30 | 1085 mm |
| Overall width less bucket | b1 | 1916 mm |
| Bucket Width | e1 | 2134 mm |
| Ground clearance | m4 | 254 mm |
| Overall length - Less Bucket | l2 | 3173 mm |
| Clearance Radius - Front with Bucket | b18 | 2350 mm |
| Performances | | |
| Travel speed (unladen) | | 11.70 km/h |
| Travel Speed with Two-Speed Option - Maximum | | 20 km/h |
| Wheels | | |
| Standard tires | | 14.00 x 17.5 HD |
| Engine | | |
| Engine brand | | Deutz |
| Engine model | | TCD3.6 |
| Max. torque / Engine rotation | | 460 Nm / 1600 rpm |
| Power source | | Battery |
| Engine power (Hp / kW) | | 114 Hp / 85 kW |
| Starter | | 4 kW |
| Hydraulics | | |
| Standard flow - Auxiliary hydraulics | | 94.60 l/min |
| Auxiliary Hydraulic Pressure | | 237.86 bar |
| High-Flow Auxiliary Hydraulics - Option | | 151.40 l/min |
| High-Flow Auxiliary Hydraulics Pressure - Option | | 237.86 bar |
| Tank capacities | | |
| Fuel | | 106 l |
| Hydraulic tank capacity | | 30.30 l |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes