

Technical sheet :

# 3350VT

---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Imperial
Operating Weight		11841 lb
Operating Capacity at 35% Tipping Load		3350 lb
Operating Capacity At 50% Tipping Load		4784 lb
Operating capacity at 35% tipping load with counterweight		3501 lb
Tipping capacity		9568 lb
Weight and dimensions		
Wheelbase	y	67 in
Overall Operating Height - Fully Raised	h27	174 in
Height to Hinge Pin - Fully Raised	h28	136 in
Dump reach - Full height	r6	37 in
Dump angle at full height	a5	41 °
Dump Height - Fully Raised	h29	105 in
Maximum Rollback Angle - Fully Raised	a4	94 °
Overall Height to top of ROPS	h17	84 in
Overall length with bucket	l16	154 in
Overall Length without Bucket	l1	123 in
Specified Height	h31	101 in
Reach at Specified Height	r4	39 in
Ground clearance	m4	9 in
Track Shoe Width	b20	18 in
Crawler base	y2	67 in
Overall width less bucket	b1	80 in
Bucket Width	e1	84 in
Clearance Radius - Front with Bucket	b18	96 in
Performances		
Ground Speed - Single Speed		6 mph
Ground Speed - Two Speed		9 mph
Engine		
Engine brand		Deutz
Engine model		TCD3.6
Engine power (Hp)		101 Hp
Engine power (kW)		74.40 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		25 US gpm
High-Flow Auxiliary Hydraulics - Option		40 US gpm
Tank capacities		
Hydraulic tank capacity		8 US gal
Fuel		38 US gal



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes