Technical sheet:

3350VT



	33300 i Oicai	335001 Gleated Oil July 29, 2023 at 10.09 AWI 010	
Capacities		Imperial	
Operating Capacity at 35% Tipping Load		3351 lb	
Operating Capacity At 50% Tipping Load		4784 lb	
Operating capacity at 35% tipping load with counterweight		3501 lb	
Tipping capacity		9568 lb	
Weight and dimensions			
Wheelbase	у	67 in	
Overall Operating Height - Fully Raised	h27	174 in	
Height to Hinge Pin - Fully Raised	h28	136 in	
Dump reach - Full height	r6	37 in	
Dump angle at full height	a5	41 °	
Dump Height - Fully Raised	h29	105 in	
Maximum Rollback Angle - Fully Raised	a4	94 °	
Overall Height to top of ROPS	h17	84 in	
Overall length with bucket	l16	154 in	
Overall Length without Bucket	l1	123 in	
Specified Height	h31	101 in	
Reach at Specified Height	r4	39 in	
Ground clearance	m4	790 ft 8 in	
Track Shoe Width	b20	18 in	
Crawler base	y2	67 in	
Overall width less bucket	b1	80 in	
Bucket Width	e1	84 in	
Clearance Radius - Front with Bucket	b18	96 in	
Performances			
Ground Speed - Single Speed		6 mph	
Ground Speed - Two Speed		9 mph	
Engine			
Engine brand		Deutz	
Engine model		TCD3.6	
Gross Power / Power		74.40 kW @ 1600 rpm	
Hydraulics			
Standard flow - Auxiliary hydraulics		25 US gpm	
High-Flow Auxiliary Hydraulics - Option		41 US gpm	
Tank capacities			
Hydraulic tank capacity		8 US gal	
Fuel tank		38 US gal	





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes