Technical sheet :





	3350VT Cre	eated on July 29, 2025 at 7:56 AM U
Capacities		Metric
Operating Capacity at 35% Tipping Load		1520 kg
Dperating Capacity At 50% Tipping Load		2170 kg
Dperating capacity at 35% tipping load with counterweight		1588 kg
Tipping capacity		4340 kg
Veight and dimensions		
Vheelbase	у	1702 mm
verall Operating Height - Fully Raised	h27	4422 mm
leight to Hinge Pin - Fully Raised	h28	3442 mm
ump reach - Full height	r6	930 mm
)ump angle at full height	a5	41 °
ump Height - Fully Raised	h29	2667 mm
Aaximum Rollback Angle - Fully Raised	a4	94 °
Verall Height to top of ROPS	h17	2121 mm
Verall length with bucket	116	3922 mm
verall Length without Bucket	1	3124 mm
pecified Height	h31	2563 mm
each at Specified Height	r4	978 mm
round clearance	m4	241 m
rack Shoe Width	b20	450 mm
rawler base	y2	1702 mm
verall width less bucket	b1	2032 mm
ucket Width	e1	2134 mm
learance Radius - Front with Bucket	b18	2426 mm
erformances		
round Speed - Single Speed		10 km/h
round Speed - Two Speed		14.80 km/h
ngine		
ngine brand		Deutz
ngine model		TCD3.6
ross Power / Power		74.40 kW @ 1600 rpm
ydraulics		
tandard flow - Auxiliary hydraulics		94.60 l/min
ligh-Flow Auxiliary Hydraulics - Option		155 l/min
ank capacities		
łydraulic tank capacity		30.30 l
uel tank		143.80 l



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes