Technical sheet:

## **3350VT**



	3350V1 GE	3350VT Created Off July 29, 2025 at 10.54 AM Of	
Capacities		Metric	
Operating Capacity at 35% Tipping Load		1520 kg	
Operating Capacity At 50% Tipping Load		2170 kg	
Operating capacity at 35% tipping load with counterweight		1588 kg	
Tipping capacity		4340 kg	
Weight and dimensions			
Wheelbase	у	1702 mm	
Overall Operating Height - Fully Raised	h27	4422 mm	
Height to Hinge Pin - Fully Raised	h28	3442 mm	
Dump reach - Full height	r6	930 mm	
Dump angle at full height	a5	41 °	
Dump Height - Fully Raised	h29	2667 mm	
Maximum Rollback Angle - Fully Raised	a4	94 °	
Overall Height to top of ROPS	h17	2121 mm	
Overall length with bucket	l16	3922 mm	
Overall Length without Bucket	l1	3124 mm	
Specified Height	h31	2563 mm	
Reach at Specified Height	r4	978 mm	
Ground clearance	m4	241 m	
Track Shoe Width	b20	450 mm	
Crawler base	y2	1702 mm	
Overall width less bucket	b1	2032 mm	
Bucket Width	e1	2134 mm	
Clearance Radius - Front with Bucket	b18	2426 mm	
Performances			
Ground Speed - Single Speed		10 km/h	
Ground Speed - Two Speed		14.80 km/h	
Engine			
Engine brand		Deutz	
Engine model		TCD3.6	
Gross Power / Power		74.40 kW @ 1600 rpm	
Hydraulics			
Standard flow - Auxiliary hydraulics		94.60 l/min	
High-Flow Auxiliary Hydraulics - Option		155 l/min	
Tank capacities			
Hydraulic tank capacity		30.30 l	
Fuel tank		143.80 l	





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes