Technical sheet:

3600VT



Operating Capacity at 55% Tipping Load 1633 kg Operating Capacity at 55% Tipping Load 2332 kg Operating capacity at 55% Tipping Load with counterweight 4666 kg Vilopit and differential and stream of the stream of		3600V I	Cleated Off July 26, 2023 at 4.40 PM OTC
Operating Capacity At 50% Tipping Load 2332 kg Operating capacity at 55% tipping load with counterweight 1700 kg Tipping capacity 4666 kg Welght and dimensions y Wheelbase y 1702 mm Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Rin - Fully Raised dp1 930 mm Bump angle af full height a5 41 * Dump Height Tolky Raised h29 2667 mm Overall Length without Rusked h17 2121 mm Overall Height to top of ROPS h17 2121 mm Overall Height with bucket 116 3968 mm Overall Height without Rusket 11 3173 mm Specified Height #4 978 mm Ground Clearance m4 241 m Creawer base m4 241 m Creawer base m4 241 m Overall width less bucket b1 2932 mm Bucket Width e1 2134 mm Clearance Raidus - Front with Bucket p1 14.80 km/h <td>Capacities</td> <td></td> <td>Metric</td>	Capacities		Metric
Operating capacity at 35% tipping load with counterweight 1700 kg Tipping capacity 4666 kg Weelplate and dimensions ************************************	Operating Capacity at 35% Tipping Load		1633 kg
Tipping capacity 4666 kg Weight and dimensions Command of the process of the p	Operating Capacity At 50% Tipping Load		2332 kg
Weight and dimensions y 1702 mm Wheelbase y 1702 mm Overall Details Height - Fully Raised h28 3442 mm Height to Hinge Pin - Fully Raised h28 3442 mm Breach - Fully Raised dp1 930 mm Dump angle aff the Height a5 41 * Dump Height - Fully Raised h29 2667 mm Owerall Height toop of ROPS h17 2121 mm Overall Length without bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height h31 2563 mm Ground Elearance m4 978 mm Ground Elearance m4 241 m 2702 mm Overall widh less bucket b1 2032 mm Bucket Width e1 2032 mm Bucket Width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance b18 2426 mm Felformances <t< td=""><td>Operating capacity at 35% tipping load with counterweight</td><td></td><td>1700 kg</td></t<>	Operating capacity at 35% tipping load with counterweight		1700 kg
Wheelbase y 1702 mm Overall Departing Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 ° Dump Height - Fully Raised h29 2657 mm Overall Height to top of ROPS h17 2121 mm Overall Height to top of ROPS h17 2121 mm Overall length with bucket I16 3958 mm Overall Height dividuot Bucket I1 3173 mm Specified Height h31 2563 mm Specified Height h31 2593 mm Ground Speck Michael p3 241 m Crawler base y2 1702 mm Overall width less bucket e1 2134 mm Clearance Radius - Front with Bucket <td>Tipping capacity</td> <td></td> <td>4666 kg</td>	Tipping capacity		4666 kg
Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump Height 1 Height a5 41 ° Dump Height - Fully Raised h29 2667 mm Overall Height Hot Dorp ROPS h17 2121 mm Overall Height with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Ground clearance m4 241 m Growler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b1 2426 mm Performances 10 km/h 14 k0 km/h Ground Speed - Single Speed 10 km/h 14 k0 km/h Ground Speed - Front with Bucket 2 bcutz 15 k0 km/h	Weight and dimensions		
Height to Hinge Pin Fully Raised	Wheelbase	у	1702 mm
Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 ** Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Height but bucket l16 3968 mm Overall Length without Bucket l16 3968 mm Overall Length without Bucket l1 3173 mm Specified Height r4 978 mm Ground Clearance m4 241 m Ground Clearance m4 241 m Creawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances B1 2426 mm Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 10 km/h 14.80 km/h Engine brand Deutz 103.6 Engine model 85 kW 41 kmin Engine model 85 kW	Overall Operating Height - Fully Raised	h27	4422 mm
Dump angle at full height a5 41 * Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Height without Bucket l16 3968 mm Overall Length without Bucket l1 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground Clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 21344 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 10 10 km/h Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Two Speed 14.80 km/h 10 km/h Engine brand Deutz 10.5 Engine model TCD3.6 35 kW Goss Power 5 55 kW Hydraulics 25 l/min Slandard flow - Auxiliary hydraulics 25 l/min <tr< td=""><td>Height to Hinge Pin - Fully Raised</td><td>h28</td><td>3442 mm</td></tr<>	Height to Hinge Pin - Fully Raised	h28	3442 mm
Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 9 10 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 14.80 km/h 14.80 km/h Engine brand Deutz TCD3.6 Gross Power 85 kW 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary hydraulics - Option 30.301	Reach - Fully Raised	dp1	930 mm
Overall Height to top of ROPS h17 2121 mm Overall Length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2553 mm Reach at Specified Height r4 978 mm Ground Clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 518 2426 mm Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Two Speed 11 km/h 14.80 km/h Engine brand Deutz 10 km/h Engine model TCD3.6 85 kW Gross Power 85 kW 41 l/min Hydraulics 25 l/min 41 l/min Tank capacities 9 30.30 l	Dump angle at full height	a5	41 °
Overall length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2456 mm Performances b18 2456 mm Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 10 km/h 14.80 km/h Engine Engine brand Deutz Engine model TC03.6 85 kW Gross Power B5 kW 25 l/min Hydraulics 25 l/min High-Flow Auxiliary hydraulics - Option 41 l/min Tank capacities 30.30 l	Dump Height - Fully Raised	h29	2667 mm
Overall Leight without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height rd 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances TO 10 km/h Ground Speed - Single Speed 10 km/h 10 km/h Fengine 11 2032 mm Engine brand Deutz 10 km/h Engine model TCD3.6 35 kW Gross Power 85 kW 35 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity 30.30 l	Overall Height to top of ROPS	h17	2121 mm
Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances B18 2426 mm Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Two Speed 14.80 km/h 10 km/h Engline Deutz 10 km/h 10 km/h 10 km/h Engline brand Performance 10 km/h 10 km/h<	Overall length with bucket	116	3968 mm
Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances TO km/h 44.80 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 14.80 km/h 14.80 km/h Engine Deutz TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 30.30 l	Overall Length without Bucket	l1	3173 mm
Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Tend of the mide of	Specified Height	h31	2563 mm
Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 30.30 l	Reach at Specified Height	r4	978 mm
Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 30.30 l	Ground clearance	m4	241 m
Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics 25 l/min Standard flow - Auxiliary Hydraulics - Option 41 l/min Tank capacities 30.30 l	Crawler base	y2	1702 mm
Clearance Radius - Front with Bucket b18 2426 mm Performances 10 km/h Ground Speed - Single Speed 11 km/h Ground Speed - Two Speed 14 k90 km/h Engine 15 model 15 model Gross Power 15 model 15 model Gross Power 15 model 15 model Gross Power 15 model 15 model Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 15 model Hydraulic tank capacity 30.30 l	Overall width less bucket	b1	2032 mm
Performances In the mode of Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Image: Company of Speed Image: Company of Speed Engine brand Image: Company of Speed Image: Company of Speed Engine model TCD3.6 Image: Company of Speed Gross Power 85 kW Image: Company of Speed Hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Image: Company of Speed Hydraulic tank capacity 30.30 l	Bucket Width	e1	2134 mm
Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine brand Engine model Engine model Gross Power Hydraulics Standard flow - Auxiliary hydraulics - Option Tank capacity Hydraulic tank capacity 10 km/h 14.80 km/h 14.80 km/h Deutz TCD3.6 Set W Hydraulic Set W 15 l/min 16 l/min 17 l/min 18 l	Clearance Radius - Front with Bucket	b18	2426 mm
Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity	Performances		
Engine brand Engine brand Engine model Engine model Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics - Option Tank capacities Hydraulic tank capacity Standard to the capacity Standard to the capacity St	Ground Speed - Single Speed		10 km/h
Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity 30.30 l	Ground Speed - Two Speed		14.80 km/h
Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity 30.30 l	Engine		
Goss Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 925 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 947 draulics 41 l/min 95 draulics 95 draulic	Engine brand		Deutz
Hydraulics Standard flow - Auxiliary hydraulics 125 I/min High-Flow Auxiliary Hydraulics - Option 141 I/min Tank capacities Hydraulic tank capacity 30.30 I	Engine model		TCD3.6
Standard flow - Auxiliary hydraulics High-Flow Auxiliary Hydraulics - Option Tank capacities Hydraulic tank capacity 30.30 I	Gross Power		85 kW
High-Flow Auxiliary Hydraulics - Option 41 I/min Tank capacities	Hydraulics		
Tank capacities Hydraulic tank capacity 30.30 I	Standard flow - Auxiliary hydraulics		25 l/min
Hydraulic tank capacity 30.30 I	High-Flow Auxiliary Hydraulics - Option		41 l/min
	Tank capacities		
Fuel tank	Hydraulic tank capacity		30.30 I
	Fuel tank		143.80 l





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes