Technical sheet:

3600VT



Departing Capacity at 35% Tipping Load 1633 kg 2332 kg 233		3600VT U	eated on July 29, 2025 at 7.52 AM UTC
Departing Capacity At 50% Tipping Load 2332 kg 71700 kg 71	Capacities		Metric
Departing capacity at 35% tipping load with counterweight	Operating Capacity at 35% Tipping Load		1633 kg
	Operating Capacity At 50% Tipping Load		2332 kg
Welpht and dimensions y 1702 mm Wheelbase y 1702 mm Wheelbase h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at It lieight a5 41 ** Dump Height - Fully Raised h29 2667 mm Overall Height to por RoPS h17 2121 mm Overall Height without bucket 116 3968 mm Overall Height without Bucket 11 3173 mm Operall Height without Bucket in the second at Specified Height h31 2563 mm Reach at Specified Height r4 978 mm 787 mm Operall width less bucket r4 978 mm 787 mm Operall width less bucket p1 2032 mm 2022 mm Outerall width less bucket p1 2032 mm 2022 mm Outerall width less bucket p1 2032 mm 2022 mm Overall width less bucket p1 2032 mm 2022 mm Overall width less bucket	Operating capacity at 35% tipping load with counterweight		1700 kg
Wheelbase y 1702 mm Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 ** Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2553 mm Reach at Specified Height r4 978 mm Reach at Specified Height r4 978 mm Storout Clearance r4 978 mm Overall width less bucket b1 2032 mm Ducket Width e1 2032 mm Ducket Width e1 2134 mm Dictations Readius - Front with Bucket b1 2032 mm Bucket Width e1 2134 mm Dictation Speed 10 km/h 14.80 km/h Storout Speed	Tipping capacity		4666 kg
Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised dp1 930 mm Oump Height - Fully Raised dp1 930 mm Oump Height - Fully Raised h29 2667 mm Oump Height - Fully Raised h29 2667 mm Ouerall Height storp of ROPS h17 2121 mm Overall Height without Bucket 116 3968 mm Overall Leight without Bucket 11 3173 mm Operating Height - Fully Raised h21 3768 mm Overall Leight without Bucket 11 3173 mm Overall Height without Bucket #1 3178 mm Operating Height - Fully Raised #1 3178 mm Overall Leight without Bucket #4 978 mm Ground Clearance m4 241 m Oround Clearance m4 241 m Overall with less bucket b1 2032 mm Overall with less bucket b18 2426 mm Overall with less bucket b18 2426 mm Oround Speed - Single Speed 10 km/h </td <td>Weight and dimensions</td> <td></td> <td></td>	Weight and dimensions		
Height to Hinge Pin - Fully Raised	Wheelbase	у	1702 mm
Reach - Fully Raised	Overall Operating Height - Fully Raised	h27	4422 mm
Dump angle at full height a5 41° Dump Height Fully Raised h29 2667 mm Dverall Height to top of ROPS h17 2121 mm Overall Height with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Seach at Specified Height r4 978 mm Ground Clearance m4 241 m Crawler base y2 1702 mm Overall with less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances b18 2426 mm Performances 10 km/h 3000 Mm/h Gound Speed - Single Speed 10 km/h 3000 Mm/h Engine brand Deutz 100.6 Engine model TCD3.6 3000 Mm/h Stores Power 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Hydrauli	Height to Hinge Pin - Fully Raised	h28	3442 mm
Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Leight with bucket 116 3968 mm Overall Leight without Bucket 11 3173 mm Specified Height h31 2553 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crowler base y2 1702 mm Overall Width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 5 10 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 10 km/h 14.80 km/h Engine brand Deutz 100.36 Engine model TCD3.6 35 kW Stross Power 85 kW 41 l/min Hydraulics 25 l/min High-Flow Auxiliary hydraulics - Option 41 l/min Hydraulic tank capacities 30.30 l	Reach - Fully Raised	dp1	930 mm
Overall Height to top of ROPS h17 2121 mm Overall Length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2569 mm Ground Clearance m4 978 mm Ground Clearance m4 241 m Overall Widh less bucket b1 2032 mm Overall Widh less buc	Dump angle at full height	a5	41 °
Overall length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances TOURS AND	Dump Height - Fully Raised	h29	2667 mm
11 3173 mm	Overall Height to top of ROPS	h17	2121 mm
Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground Clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 10 km/h Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Engine Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics 25 l/min High-Flow Auxiliary hydraulics - Option 41 l/min Fank capacities 41 l/min	Overall length with bucket	l16	3968 mm
Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Engine brand Deutz Engine model TCD3.6 Gross Power Hydraulics Standard flow - Auxiliary hydraulics - Option 25 I/min High-Flow Auxiliary Hydraulics - Option 41 I/min Tank capacities Hydraulic tank capacity 30.30 I	Overall Length without Bucket	l1	3173 mm
Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances TOR 10 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 14.80 km/h TOR Engine TCD3.6 TCD3.6 Engine brand TCD3.6 85 kW Engine model TCD3.6 85 kW Engine brand flow - Auxiliary hydraulics 25 l/min Engine brand flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 41 l/min Hydraulic tank capacity 30.30 l	Specified Height	h31	2563 mm
Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances	Reach at Specified Height	r4	978 mm
Deverall width less bucket Bucket Width e1 2134 mm Clearance Radius - Front with Bucket Performances Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine Engine Engine Web Engine E	Ground clearance	m4	241 m
Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine Engine Engine brand Engine wodel Engine Engin	Crawler base	y2	1702 mm
Clearance Radius - Front with Bucket Performances Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine Engine Engine brand Engine brand Engine model Gross Power Hydraulics Standard flow - Auxiliary Hydraulics - Option Tank capacities Hydraulic tank capacity b 18 2426 mm 10 km/h 14.80 km/h 14.80	Overall width less bucket	b1	2032 mm
Performances Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine Engine brand Engine model Engine model Gross Power Hydraulics Standard flow - Auxiliary Hydraulics - Option Tank capacity Hydraulic tank capacity Standard tank capacity Standard tank capacity 10 km/h 14.80 km/h 14.	Bucket Width	e1	2134 mm
Ground Speed - Single Speed Ground Speed - Two Speed Engine Engine Engine brand Engine model Gross Power Hydraulics Standard flow - Auxiliary Hydraulics - Option Tank capacities Hydraulic tank capacity 10 km/h 14.80 km/h 15.80 km/h 16.80	Clearance Radius - Front with Bucket	b18	2426 mm
Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics Standard flow - Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity	Performances		
Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 I/min High-Flow Auxiliary Hydraulics - Option 41 I/min Tank capacities Hydraulic tank capacity 30.30 I	Ground Speed - Single Speed		10 km/h
Deutz	Ground Speed - Two Speed		14.80 km/h
Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics Standard flow - Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity	Engine En		
Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 925 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacitles 94 ydraulic tank capacity 30.30 l	Engine brand		Deutz
Hydraulics Standard flow - Auxiliary hydraulics High-Flow Auxiliary Hydraulics - Option Tank capacities Hydraulic tank capacity 30.30 I	Engine model		TCD3.6
Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacitles 9 Hydraulic tank capacity 30.30 l	Gross Power		85 kW
High-Flow Auxiliary Hydraulics - Option 41 I/min Tank capacities 41 I/min Hydraulic tank capacity 30.30 I	Hydraulics		
Tank capacities Hydraulic tank capacity 30.30 I	Standard flow - Auxiliary hydraulics		25 l/min
Hydraulic tank capacity 30.30 I	High-Flow Auxiliary Hydraulics - Option		41 l/min
	Tank capacities		
Fuel tank	Hydraulic tank capacity		30.30 l
	Fuel tank		143.80 l





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes