

Technical sheet :

3600VT



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|---|-----|--------------|
| Operating Weight | | 5516 kg |
| Operating Capacity at 35% Tipping Load | | 1633 kg |
| Operating Capacity At 50% Tipping Load | | 2332 kg |
| Operating capacity at 35% tipping load with counterweight | | 1700 kg |
| Tipping capacity | | 4666 kg |
| Weight and dimensions | | |
| Wheelbase | y | 1702 mm |
| Overall Operating Height - Fully Raised | h27 | 4422 mm |
| Height to Hinge Pin - Fully Raised | h28 | 3442 mm |
| Reach - Fully Raised | dp1 | 930 mm |
| Dump angle at full height | a5 | 41 ° |
| Dump Height - Fully Raised | h29 | 2667 mm |
| Overall Height to top of ROPS | h17 | 2121 mm |
| Overall length with bucket | l16 | 3968 mm |
| Overall Length without Bucket | l1 | 3173 mm |
| Specified Height | h31 | 2563 mm |
| Reach at Specified Height | r4 | 978 mm |
| Ground clearance | m4 | 241 mm |
| Crawler base | y2 | 1702 mm |
| Overall width less bucket | b1 | 2032 mm |
| Bucket Width | e1 | 2134 mm |
| Clearance Radius - Front with Bucket | b18 | 2426 mm |
| Performances | | |
| Ground Speed - Single Speed | | 10 km/h |
| Ground Speed - Two Speed | | 14.80 km/h |
| Engine | | |
| Engine brand | | Deutz |
| Engine model | | TCD3.6 |
| Engine power (Hp) | | 114 Hp |
| Engine power (kW) | | 85 kW |
| Hydraulics | | |
| Standard flow - Auxiliary hydraulics | | 151.40 l/min |
| High-Flow Auxiliary Hydraulics - Option | | 94.60 l/min |
| Tank capacities | | |
| Hydraulic tank capacity | | 30.30 l |
| Fuel | | 143.80 l |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes