Technical sheet:

3600VT



Operating Capacity at 35% Tipping Load 1633 kg Operating Capacity 41 50% Tipping Load 2332 kg Operating Capacity 41 50% Tipping Load with counterweight 1700 kg Tipping capacity 4666 kg Weight and dimensions Weight and dimensions Wheelbase y 1702 mm Overall Operating Height - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump allegia at full height a5 41* Dump deight - Fully Raised dp1 930 mm Dump allegia at full height a5 41* Owerall Length without Busket h16 366 mm Overall Length without Busket 116 3968 mm Overall Length without Busket 11 373 mm Specified Height h31 2563 mm Ground Specified Height h1 291 mm Ground Specified Height h1		3600V I	Gleated Oil July 29, 2023 at 0.13 PM OTC
Operating Capacity At 50% Tipping Load 2332 kg Operating Capacity At 50% tipping Ioad with counteweight 1700 kg Tipping capacity 4666 kg Weight and dimensions y 1702 mm Wheelbase y 1702 mm Overall Operating Height - Fully Raised h27 4422 mm Height to Hippe Rin - Fully Raised dp1 930 mm Dump Angle at I'll height a5 41 * Dump Height - Fully Raised h29 2667 mm Overall Height with Use of ROPS h17 2121 mm Overall Height with Use of ROPS h17 2121 mm Overall Height with Use ket 11 3968 mm Overall Height with Use ket 11 3173 mm Specified Height j 478 mm Reach at Specified Height j 978 mm Ground I with less bucket j 1792 mm Overall with less bucket j 292 mm Bucket Width j 293 mm Bucket Width j 293 mm Bucket Width j	Capacities		Metric
Operating capacity at 35% tipping load with counterweight 1700 kg Tipping capacity 4666 kg Weelbase y 1702 mm Wheelbase y 1702 mm Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height h29 2667 mm Owerall Height to boy of RDPS h17 2121 mm Owerall Length without Bucket 116 3958 mm Overall Height to bucket 116 3958 mm Overall Height to bucket 11 3173 mm Specified Height 44 978 mm Ground Length without Bucket 11 3173 mm Specified Height 44 978 mm Ground Learnace m4 241 m Crewlet base y2 1702 mm Overall Width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearnace Radius - Front with Bucket b1	Operating Capacity at 35% Tipping Load		1633 kg
Tipping capacity	Operating Capacity At 50% Tipping Load		2332 kg
Weight and dimensions y 1702 mm Wheelbase y 1702 mm Overall Deraing Height - Fully Raised h28 3442 mm Height to Hinge Pin - Fully Raised h28 3442 mm Beach - Fully Raised dp1 930 mm Dump angle at full height a5 41 * Dump Height - Fully Raised h29 2667 mm Owerall Length without bucket h17 2121 mm Overall Length without Bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height h31 2563 mm Ground Clearance m4 978 mm Ground Expectified Height h31 2563 mm Ground Speck Expectified Height h1 978 mm Ground Expectified Height h31 2563 mm Ground Expectified Height h1 978 mm Ground Expectified Height h1 978 mm Ground Expectified Height h1 972 mm	Operating capacity at 35% tipping load with counterweight		1700 kg
Wheelbase y 1702 mm Overall Departing Height - Fully Raised h27 4422 mm Height De Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41° Dump alged at Full height h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall length with bucket 116 3968 mm Overall length with bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height h31 2563 mm Specified Height base y2 1702 mm Overall with less bucket y2 1702 mm Overall with less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket e1 2134 mm Clearance Radius - Front with Bucket e1 10 km/h Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Two Speed 10 km/h 10 km/h </td <td>Tipping capacity</td> <td></td> <td>4666 kg</td>	Tipping capacity		4666 kg
Overall Operating Height - Fully Raised h27 4422 mm Height to Hinge Pin - Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 * Dump Height - Fully Raised h29 2667 mm Overall Height sto top of ROPS h17 2121 mm Overall Height without Bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height j4 978 mm Ground clearance m4 253 mm Ground clearance m4 241 m Growled base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b1 2022 mm Performances 10 km/h 14 k0 km/h Ground Speed - Single Speed 10 km/h 14 k0 km/h Ground Speed - Frow Speed 10 km/h 14 k0 km/h Engine 25 l/min 25 l/min E	Weight and dimensions		
Height to Hinge Pin Fully Raised h28 3442 mm Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 * Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Height to top of ROPS h16 3968 mm Overall Leight without Bucket l16 3968 mm Overall Leight without Bucket l1 3173 mm Specified Height r4 978 mm Ground clearance r4 978 mm Ground clearance r4 271 mm Overall width less bucket r4 978 mm Ground Speed - Width e1 2032 mm Bucket Width e1 2032 mm Performances p1 2134 mm Clearance Radius - Front with Bucket p1 214 mm Performances p1 11 km/h Ground Speed - Single Speed p1 12 km/h Engine p2 12 km/h Engine brand p2 2	Wheelbase	у	1702 mm
Reach - Fully Raised dp1 930 mm Dump angle at full height a5 41 ** Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Length with bucket l16 3968 mm Overall Length without Bucket l16 3968 mm Overall Length without Bucket l1 3173 mm Specified Height r4 978 mm Ground Clearance m4 241 m Ground Clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances B1 2426 mm Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed B1 25 km Engine brand B2 B2 B2 Engine model	Overall Operating Height - Fully Raised	h27	4422 mm
Dump angle at full height a5 41 ° Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Height with bucket h16 3968 mm Overall Length with out Bucket l1 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances b18 2426 mm Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Two Speed 1 km/h 10 km/h Engine brand 5 5 5 kW Engine model 5 6 5 kW Goss Power 5 25 l/min High-Flow Auxillary hydraulics 25 l/min 41 l/min Tink Capacitie	Height to Hinge Pin - Fully Raised	h28	3442 mm
Dump Height - Fully Raised h29 2667 mm Overall Height to top of ROPS h17 2121 mm Overall Leight with bucket 116 3968 mm Overall Leight with bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground Clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 10 km/h 14.80 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 14.80 km/h 14.80 km/h Engine Brand Deutz 12.80 km/h Engine model TCD3.6 85 kW Gross Power 85 kW 85 kW Hydraulics 25 l/min High-Flow Auxiliary hydraulics - Option 25 l/min Tonk capacites 30.30 l	Reach - Fully Raised	dp1	930 mm
Overall Height to top of ROPS h17 2121 mm Overall Length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2553 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crewier base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 10 km/h 10 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Engine 10 km/h 14.80 km/h Engine brand 5 5 15.00 km/h Engine model 5 6 85 kW Hydraulics 5 85 kW High-Flow Auxiliary hydraulics - Option 41 l/min 11.0 km/h Tank capacities 41 l/min 1.0 km/h	Dump angle at full height	a5	41 °
Overall length with bucket 116 3968 mm Overall Length without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 246 mm Performances b18 246 mm Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 1 12.80 km/h Engine 5 5 12.80 km/h Engine brand 5 5 12.80 km/h 12.80 km/h Engine model 5 60 ss Fower 85 kW 14.80 km/h 14.80 km/h 12.80 km/h <	Dump Height - Fully Raised	h29	2667 mm
Overall Leight without Bucket 11 3173 mm Specified Height h31 2563 mm Reach at Specified Height rd 978 mm Ground clearance m4 241 m Crowler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances 5 10 km/h Ground Speed - Single Speed 10 km/h 10 km/h Ground Speed - Ymo Speed 1 2 Engine 5 10 km/h Engine brand 5 10 km/h Engine model 7 10 beutz Engine model 7 35 kW Hydraulics 85 kW 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities 41 l/min Hydraulic tank capacity 30.30 l	Overall Height to top of ROPS	h17	2121 mm
Specified Height h31 2563 mm Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances B18 2426 mm Ground Speed - Single Speed 10 km/h 41.80 km/h Ground Speed - Two Speed 14.80 km/h 41.80 km/h Engline B18 B2426 mm B18 B2426 mm Engline brand B18 B2426 mm B18 B2426 mm B18 B1	Overall length with bucket	l16	3968 mm
Reach at Specified Height r4 978 mm Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances TO km/h 10 km/h Ground Speed - Single Speed 10 km/h 14.80 km/h Ground Speed - Two Speed 14.80 km/h 10 km/h Engine Deutz TCD3.6 Engine model TCD3.6 85 kW Gross Power 85 kW 25 l/min Hydraulics 25 l/min 41 l/min Tank capacities 41 l/min 41 l/min	Overall Length without Bucket	l1	3173 mm
Ground clearance m4 241 m Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 25 l/min Tank capacities 41 l/min Hydraulic tank capacity 30.30 l	Specified Height	h31	2563 mm
Crawler base y2 1702 mm Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power TCD3.6 Gross Power 5 Hydraulics 25 l/min Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 30.30 l	Reach at Specified Height	r4	978 mm
Overall width less bucket b1 2032 mm Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Engine model \$85 kW Gross Power \$85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities 41 l/min Hydraulic tank capacity 30.30 l	Ground clearance	m4	241 m
Bucket Width e1 2134 mm Clearance Radius - Front with Bucket b18 2426 mm Performances Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine 5 14.80 km/h Engine brand 5 Deutz Engine model 7CD3.6 35 kW Gross Power 85 kW 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities 41 l/min Hydraulic tank capacity 30.30 l	Crawler base	y2	1702 mm
Clearance Radius - Front with Bucketb182426 mmPerformancesClearance Radius - Front with BucketLear CommenderGround Speed - Single Speed10 km/hGround Speed - Two Speed14.80 km/hEngine14.80 km/hEngine brandDeutzEngine modelTCD3.6Gross Power85 kWHydraulics\$25 l/minStandard flow - Auxiliary hydraulics - Option41 l/minTank capacities41 l/minHydraulic tank capacity30.30 l	Overall width less bucket	b1	2032 mm
PerformancesCound Speed - Single Speed10 km/hGround Speed - Two Speed14.80 km/hEngine14.80 km/hEngine brandDeutzEngine modelTCD3.6Gross Power85 kWHydraulics85 kWStandard flow - Auxiliary hydraulics25 l/minHigh-Flow Auxiliary Hydraulics - Option41 l/minTank capacities41 l/minHydraulic tank capacity30.30 l	Bucket Width	e1	2134 mm
Ground Speed - Single Speed 10 km/h Ground Speed - Two Speed 14.80 km/h Engine 50 cm Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics 25 l/min Standard flow - Auxiliary hydraulics - Option 41 l/min Tank capacities 30.30 l	Clearance Radius - Front with Bucket	b18	2426 mm
Ground Speed - Two Speed 14.80 km/h Engine Deutz Engine brand TCD3.6 Gross Power 85 kW Hydraulics TCD3.6 Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity 30.30 l	Performances		
Engine Common of the state of	Ground Speed - Single Speed		10 km/h
Engine brand Deutz Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity 30.30 l	Ground Speed - Two Speed		14.80 km/h
Engine model TCD3.6 Gross Power 85 kW Hydraulics Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Hydraulic tank capacity Hydraulic tank capacity 30.30 l	Engine		
Gos S Power 85 kW Hydraulics 55 l/min Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities 80.30 l Hydraulic tank capacity 30.30 l	Engine brand		Deutz
Hydraulics 25 I/min Standard flow - Auxiliary hydraulics 41 I/min High-Flow Auxiliary Hydraulics - Option 43 I/min Tank capacities 30.30 I	Engine model		TCD3.6
Standard flow - Auxiliary hydraulics 25 l/min High-Flow Auxiliary Hydraulics - Option 41 l/min Tank capacities Uddaulic tank capacity 30.30 l	Gross Power		85 kW
High-Flow Auxiliary Hydraulics - Option 41 I/min Tank capacities Hydraulic tank capacity 30.30 I	Hydraulics		
Tank capacities Hydraulic tank capacity 30.30 I	Standard flow - Auxiliary hydraulics		25 l/min
Hydraulic tank capacity 30.30 I	High-Flow Auxiliary Hydraulics - Option		41 I/min
	Tank capacities		
Fuel tank 143.80 I	Hydraulic tank capacity		30.30 I
	Fuel tank		143.80 l





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes